

GRAINGER APPROVED GRAINGERCHOICE

Pressure Gauge, 0 to 400 psi Range, 1/4 in MNPT, ±1.00% Gauge Accuracy

Item #18C753 Mfr. Model #18C753  
UNSPSC #41112403 Catalog Group #G3995  
Catalog Page #574

Country of Origin China. Country of Origin is subject to change.

Contractor Gauges  
• 4-1/2" dial Accuracy: ±1%  
Connection/internal material: copper



⚠ Product is Discontinued

Alternate Available  
Alternate products may not be identical in style or function to original selection.



WINTERS

Pressure Gauge, 0 to 400 psi Range, 1/4 in MNPT, +/-1.00% Gauge Accuracy

Item # 491C48

Web Price

**\$27.94** / each

Technical Specs

|                           |                        |                                         |                      |
|---------------------------|------------------------|-----------------------------------------|----------------------|
| Item                      | Pressure Gauge         | Gauge Accuracy                          | +/-1.00%             |
| Gauge Application         | Mechanical Contractors | Pressure and Vacuum Gauge Type          | Pressure Gauge       |
| Gauge Nominal Dial Size   | 4 1/2 in               | Gauge Panel Mountable                   | No                   |
| Basic Gauge Case Material | Stainless Steel        | Liquid Filled                           | No                   |
| Basic Gauge Wetted Parts  | Copper                 | Gauge Primary Range Smallest Graduation | 5                    |
| Gauge Connection Type     | MNPT                   | Gauge Case Material                     | Stainless Steel      |
| Gauge Connection Size     | 1/4 in                 | Gauge Case Color                        | Stainless Steel      |
| Gauge Connection Location | Bottom                 | Basic Gauge Socket Material             | Copper               |
| Gauge Primary Range Units | psi                    | Gauge Socket Material                   | Copper Alloy HPb59-1 |

|                            |                              |
|----------------------------|------------------------------|
| Gauge Primary Range Values | 0 to 400                     |
| Gauge Sensor Material      | Copper Alloy                 |
| Gauge Lens Material        | Acrylic                      |
| Basic Gauge Lens Material  | Plastic                      |
| Operating Temp. Range      | -40 Degrees to 200 Degrees F |

|                                  |                                                                             |
|----------------------------------|-----------------------------------------------------------------------------|
| Basic Gauge Sensor Material      | Copper                                                                      |
| For Use With                     | Non-Explosive Gas Or Liquid That Do Not Crystalize And Corrode Copper Alloy |
| Calibration Certificate Included | No                                                                          |
| Series                           | Y120SS                                                                      |

## Compliance and Restrictions

 **WARNING** This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Documentation

 [Grainger Choice Pressure and Vacuum Gauge Selection Guide](#)