



APPROVED VENDOR Commercial Pressure Gauge: 0 to 160 psi, 2 in Dial, 1/4 in NPT Male, Bottom, Plastic

Item **4FLU2** Mfr. Model **4FLU2**

Web Price 
\$12.82 / each

Qty
1

Add to Cart

☒ Ship

☐ Pickup

Expected to arrive **Wed. Dec 11.**

Ship to **78613** | [Change](#)

Shipping Weight **0.16 lbs**

[Ship Availability Terms](#)

[Add to List](#)

Product Details

Catalog Page [547](#) Catalog Group [D1338](#)

Brand **APPROVED VENDOR**

Pressure Gauge Type **Commercial Pressure Gauge**

Pressure Range Type **Pressure**

Scale Type **Dual**

Pressure Range **0 to 160 psi**

Secondary Range **0 to 1,100 kPa**

Nominal Dial Size **2 in**

Process Connection Location **Bottom**

Process Connection Size **1/4 in**

Process Connection Type **NPT**

Process Connection Gender **Male**

Case Material **Plastic**

Gauge Application **General-Purpose Case**

Gauge Wetted Parts **Brass / Bronze**

Lens Material - Gauge **Plastic**

Primary Pressure Range **0 to 160**

Primary Scale Minor Graduations **1; 2**

Primary Scale Units **psi**

Process Connection **1/4 in NPT Male**

Secondary Pressure Range **0 to 1,100**

Secondary Scale Units **kPa**

Compliance & Restrictions

 **WARNING:** Cancer and
Reproductive Harm -
www.P65Warnings.ca.gov

Documents

 [Grainger Choice Pressure and
Vacuum Gauge Selection Guide](#)

 [Chat with an Agent](#)

Mounting Type	Stem-Mount
Wetted Parts Material	Brass/Bronze
Gauge Case Material	ABS Plastic
Case Color	Black
Lens Material	Acrylic
Accuracy	±3-2-3%
Accuracy Scale	Mid-Scale
Primary Graduations	1; 2
Ambient Operating Temperature Range	-40° to 150°F
Dial Color	White
Bezel Material	Crimped Stainless Steel
Removable Bezel	No
Application	Test and Measurement
IP/NEMA Rating	Not Rated
Blowout Safety Back	No
Includes Vent Plug	No
Cleaned for Oxygen Service	No
Dry Dampening Feature	None
Field Fillable	No
Freeze Resistant Movement	No
Gauge Case Liquid	None
Hazardous Location Rating	Not Rated
Includes Calibration Certificate	No
Includes Mounting Hardware	No
Liquid-Filled Case	No
Non-Sparking	No
Panel-Mountable	No
Sensor Material	Bronze
Socket Material	Brass
Vibration Resistance	None
Manufacturer Part Number	4FLU2

Country of Origin **China (subject to change)**

Product Description

These utility gauges have back or bottom threaded connections. They are used for most general purpose pressure measurement and monitoring applications.

 Compatible Products



APPROVED VENDOR Thread Sealant Tape: Med Density, 1/2 in x 21 ft, White

Item **21TF27**

Web Price 
\$2.22 / each

Min. qty. of 2: **\$4.44**

Qty

2

Add to Cart

This product can only be shipped in multiples of 2.



ANTI-SEIZE TECH. Thread Seal Tape Assortment: Med Density, 1/2 in x 21 ft, Pink/Yellow

Item **2TE54**

Web Price 
\$29.00 / each

Qty

1

Add to Cart



ANTI-SEIZE TECH Pipe Thread Sealant: TFE, 9.6 fl oz, Brush-Top Can, Off-White

Item **4X222**

Web Price 
\$20.72 / each

Qty

1

Add to Cart



ANTI-SEIZE TECH. Thread Sealant Tape: POLY-TEMP® MD, Med Density, 1/2 in x 21 ft, White

Item **4X227**

Web Price 
\$2.77 / each
Min. qty. of 2: **\$5.54**

Qty

2

Add to Cart

	This product can only be shipped in multiples of 2.
--	---