


[Browse](#)
[Search](#)

ATS PRO DIFFERENTIAL PRESSURE TESTER WITH MASTER ORIFICE

Part Number: 2EM
Category: [ENGINE EQUIPMENT](#)



Hover to zoom. Click to expand



Price: \$135.95

Qty

NOTE: The ATS 2EM Differential Pressure Tester has a .040" orifice as required by Teledyne Continental SB03-3 Service Bulletin, and is the proper type of instrument to test **ALL** Teledyne Continental engines in accordance with the aforementioned bulletin. The ATS 2EM also complies Textron Lycoming SI-1191A Service Instruction and is appropriate for **ALL** Textron Lycoming engines as indicated in the Service Instruction. For all other makes of engines, consult FAA AC43.13 REV 1B for guidance in selecting the proper instrument for your engine'

The Model 2EM Differential Cylinder Pressure Tester combines the features of our popular 2E tester and a Master Orifice into one tool. Now you can conveniently check your engine's leakdown rate against its built-in calibrated standard to instantly determine if your engine's cylinder leakage is within the manufacturer's limits. Specifications: Orifice size is .040". precision gauges matched to within +/-2%. Includes 18MM Spark Plug Adapter, 24" pressure hose, and complete instructions. Protective form-fitted hard case included. Factory calibrated. Letter of certification available upon request.

3 lbs (1.5Kg) shipping weight.

Product Accessories

May we recommend the following accessories to get the most from your selected product? To include any of these items with your purchase, simply enter the desired quantity of each item before clicking the above "Buy" button.



ADAPTER, 2E PRESSURE TESTER

Part Number: 10MM

10mm plug adapter for 2E.

Price: **\$9.95** Qty



DIFFERENTIAL PRESSURE TESTER CYLINDER PLUG (12MM)

Part Number: 12MM

12MM adapter plug used with our [2E](#) and [2EM](#) Differential Pressure Testers. For engines with 12MM plugs such as the Rotax.

Price: **\$9.95** Qty

DIFFERENTIAL PRESSURE TESTER CYLINDER PLUG (14MM)