

Traceable Professional Thermohygrometer with Calibration

[Traceable](#) – Item # EW-20250-21

•	Min RH Range (%)	0
•	Max RH Range (%)	100
•	RH Accuracy	±2% RH from 40% to 60% RH; ±3% RH from 20% to 40% RH and 60% to 80% RH; ±4% RH from 0% to 20% RH and 80% to 100% RH
•	RH Resolution (%)	0.1%
•	Min Temperature (° F)	-22
•	Min Temperature (° C)	-30
•	Max Temperature (° F)	212
•	Max Temperature (° C)	100
•	Temperature Accuracy	±1.8°F; ±2.7°F above 140° and below -4°F (±1.0°C; ±1.5°C above 60° and below 19°C)
•	Temperature Resolution	0.1°
•	Min Dew Point Range (° F)	-22
•	Max Dew Point Range (° F)	212
•	Min Dew Point Range (° C)	-30
•	Max Dew Point Range (° C)	100
•	Wet Bulb	Yes
•	Response Time	<15 seconds
•	Display Type	LCD (backlit)
•	Battery	9V battery (1)
•	Height (in)	11
•	Width (in)	3
•	Depth (in)	1
•	Description	Professional Thermohygrometer with NIST Traceable Calibration

Hard carrying case, one 9 V battery, and NIST-traceable calibration report with data supplied by [InnoCal](#).