

SKU 303-3300A

0.20" AXIS OFFSET RANGE CO-AXIAL CENTER INDICATOR SET

AVAILABILITY IN STOCK
SHIPPING UPS GROUND

\$120.50



[DETAILS](#) | [SPOTLIGHT](#) | [WHAT'S INCLUDED](#) | [RELATED PRODUCTS](#)

SKU	303-3300A
MFG SKU #	303-3300A
LAYOUT SETUP CATEGORY	Center Indicators (Co-Ax & 3D)
BRAND	Shars Tool
OVERALL LENGTH	6-7/8
CONTACT POINT BALL DIAMETER	0.125"
GRADUATION	0.0005
ACCURACY	0.0002
MEASURING RANGE DIAL INDICATOR	0.15"
DIAL READING	0-50
MAXIMUM RPM	800

[FULL DETAILS](#)

PRODUCT SPOTLIGHT

–Critical surface precision ground finished

- Shank: 3/8" diameter x 7/8" length
- Feeler Ball Diameter: 1/8"
- Measuring Range: 0.200 axis offset
- Internal capacity range is 5/32 to 12" diameter and external capacity range is 0 to 12" diameter depending on the feeler
- Speed: Max 800 rpm
- Locating Accuracy: .0002" from true center
- Graduation: .0005"
- Operates at any angle, vertical or horizontal, internal or external
- Indicator remains in fixed position facing the operator while the spindle rotates

WHAT'S INCLUDED

- Coaxial indicator main body
- 2" Long internal feeler for 5/32" to 4-1/4" diameter bore
- 2" Long external feeler for 0 to 4-1/4" diameter bore
- 4" Long internal feeler for 5/32" to 8" diameter bore
- 4" Long external feeler for 0 to 8" diameter bore
- 6" Long internal feeler for 5/32" to 12" diameter bore
- 6" Long external feeler for 0 to 12" diameter bore
- Restraining stopping rod
- Fitted Case