

Micrometer Torque Wrenches



- Meets or exceeds ASME B107.300

- Non-slip metal knurling handle grip for superior hold

- Accurate in clockwise direction $\pm 3\%$ from 20% to 100% of full scale

- Thin profile, sealed tear-drop head design for access and durability

- Pull back locking collar

- Scale markings are highly visible and easy to read



PRECISION FOR

$\pm 3\%$

TORQUE ACCURACY

LOW PROFILE HEAD



FLUSH REVERSING LEVER

FLEX HEAD



FOR ACCESS

Cat. No.	Certified Model No.	Drive Size	Head Style	Primary Scale Range	Primary Scale Increments	Alt. Scale Range	Alt Scale Increments	Tooth Count	Head Thickness (in)	Head Width (in)	Overall Length (in)	Product Weight
85060	85060CERT	1/4"	Standard	30-200 in/lbs	1 in/lb	4 - 23 Nm	0.1	22	0.54	1.1	10.5	0.8
85061	85061CERT	3/8"	Standard	20-250 in/lbs	1 in/lb	5 - 29 Nm	0.2	30	0.72	1.4	14	1.95
85062	85062CERT	3/8"	Standard	10-100 ft/lbs	1 ft/lb	20 - 142 Nm	1	30	0.72	1.4	18	2.5
85063	85063CERT	1/2"	Standard	20-150 ft/lbs	1 ft/lb	34 - 210 Nm	1	32	0.81	1.75	21.9	3.1
85066	85066CERT	1/2"	Standard	30-250 ft/lbs	2 ft/lb	54 - 353 Nm	3	32	0.81	1.75	24.3	3.5
85086	85086CERT	3/8"	Flex	5-75 ft/lbs	.5 ft/lb	10 - 105 Nm	1	30	0.72	1.4	17.7	2.42
85087	85087CERT	1/2"	Flex	30-250 ft/lbs	2 ft/lb	54 - 353 Nm	3	36	0.93	1.75	25.25	3.82