

TEST INDICATORS

708, 708M, 709, 709M DIAL TEST INDICATORS WITH DOVETAIL MOUNTS

.020", .060"/0.2MM, 0.8MM

These precision test indicators offer an easy to read angled head and the flexibility of three dovetail mounts. Features include:

- Large 1-3/8" (35mm) dial diameter with angled head
- Precision gear-driven design with smooth, jeweled movement
- Replaceable contact point reverses automatically, always maintaining clockwise hand rotation
- Satin chrome finish for durability
- Contacts are frictionally adjustable and replaceable
- Revolution count hand on 708B and 709B models
- Meet or exceed ISO accuracy specification



708BZ

R708AZ

Individual Carbide Contact Points†

Part No.	EDP	Length		Ball Diameter		Fits Models
		in	mm	in	mm	
PT23942	65255			.040	1	
PT23914†	64222	13/16	20	.078	2	.0001", .0005", 0.01mm Reading Models
PT23943	65256			.120	3	
PT27024†	66239	1-23/64	34.4	.078	2	.0001", .0005", 0.01mm Reading Models
PT25577†	67294	1-5/64	28.4	.078	2	.0001", .0005", 0.01mm Reading Models
PT23953†	65868	5/8	16	.078	2	0.002mm Reading Models Only

† PT23914, PT27024, PT25577 and PT23953 furnished as standard.

‡ Length of carbide contacts must be the same as contacts normally furnished.



709BCZ

708, 709 Dial Test Indicators with Dovetail Mounts

Cat. No.	EDP	With SLC**		Grad.	Range	Dial Reading	Carbide Contact Point Length	Ball Dia.	Dial Color	Description
Cat. No.	EDP	Cat. No.	EDP							
708AZ	64212	708AZ W/SLC	66866						White	Without attachments
R708AZ	64603	R708AZ W/SLC	66867						Red	
B708AZ	64607	B708AZ W/SLC	66868	.0001"	.010"	0-5-0	13/16" (20mm)	.078" (2mm)	Black	
708ACZ	64217	708ACZ W/SLC	66869						White	With attachments*
R708ACZ	64604	R708ACZ W/SLC	66870						Red	
B708ACZ	64608	B708ACZ W/SLC	66871	.0001"	.020"	0-5-0	13/16" (20mm)	.078" (2mm)	Black	
708BZ	64213	708BZ W/SLC	66874						White	Without attachments
708BCZ	64218	708BCZ W/SLC	66875	.0001"	.020"	0-5-0	13/16" (20mm)	.078" (2mm)	White	With attachments*
709AZ	64214								White	Without attachments
R709AZ	64605								Red	
B709AZ	64609			.0005"	.030"	0-15-0	13/16" (20mm)	.078" (2mm)	Black	
709ACZ	64219								White	With attachments*
R709ACZ	64606								Red	
B709ACZ	64610								Black	
709ALZ	65857			.0005"	.050"	0-25-0	1-23/64" (34.4mm)	.078" (2mm)	White	Without attachments
709ALCZ	65858									With attachments*
709BZ	64215			.0005"	.060"	0-15-0	13/16" (20mm)	.078" (2mm)	White	Without attachments
709BCZ	64220									With attachments*

708M, 709M Dial Test Indicators with Dovetail Mounts

Cat. No.	EDP	With SLC**		Grad	Range	Dial Reading	Carbide Contact Point Length	Ball Dia.	Dial Color	Description
Cat. No.	EDP	Cat. No.	EDP							
708MAZ	65864	708MAZ W/SLC	66872	0.002mm	0.2mm	0-100-0	5/8" (16mm)	.078" (2mm)	Yellow	Without attachments
708MACZ	65865	708MACZ W/SLC	66873							With attachments*
709MAZ	64216			0.01mm	0.8mm	0-40-0	13/16" (20mm)	.078" (2mm)	Yellow	Without attachments
709MACZ	64221									With attachments*
709MALZ	67092			0.01mm	1.0mm	0-50-0	1-5/64" (28.4mm)	.078" (2mm)	Yellow	Without attachments
709MALCZ	67093									With attachments*

*Attachments include dovetail body clamp (PT22429/EDP 72441), tool post holder (PT11770A/EDP 71361), swivel post snug with dovetail indicator clamp (PT22428/EDP 72440), and snug and rod unit (Inch: PT22430/EDP 72442 or Millimeter: PT27171/EDP 66457).

** Includes redemption card for Standard Letter of Certification

