

Products

HOME > Products > Torque drivers > LTDK

Products

Torque tools
Torque Wrenches
Torque Drivers
Torque Analyzers
Torque Gauges
Vernier Calipers
Calipers
Centerline Calipers
Depth Gauges
Height Gauges

Recommend

DRT

Torque measurement multi-indicator






TCSK-99MA

Multi-function torque task manager

LTDK

Adjustable Torque Screw Driver

Clutch release prevents over-tightening, reduces fatigue.



- Comfortable grip for extended use.
 - Light weight and short overall length facilitates jobs.
- Sensitive clutch release helps the operator feel when the torque setting is reached.
- Set the required torque value and tighten, all operator tighten consistently.
 - Two phillips bit are included.
 - Various hex and box drive bits are available.
 - Use for clockwise tightening.
 - Accuracy:±3% of indicated value over the full range, clockwise.

Old Model (cN·m/N·m)	New Model (cN·m/N·m)	Range	Increment	Model (ozf·in/lbf·in)	Range	Increment	Grip dia.	Total length (without bit)	Dimensions (mm)						Weight	Included Accessory		
									Body							Bits		Extension Bar
									φmm	mm	L1	L2	φD1	φD2		φD3	g	
N1.5LTDK	CN15LTDK	1 ~ 15 cN·m	0.1 cN·m				16	107	22	10.5	5.5	14.4	16	57	No.0 No.1	KANON bits CB type		
N3LTDK	CN30LTDK	2 ~ 30 #	0.2 #															
N6LTDK	CN60LTDK	5 ~ 60 #	0.5 #				25	110	26					20	99			
N12LTDK	CN120LTDK	20 ~ 120 #	1 #	Cl 200LTDK	40 ~ 200 ozf·in	1	30								192	No.0 No.1		
N20LTDK	CN200LTDK	40 ~ 200 #	1 #					34	157	51		10				214		
N30LTDK	CN300LTDK	40 ~ 300 #	1 #	PI 30LTDK PI 50LTDK	4 ~ 30 lbf·in	0.1	34									436	No.1 No.2	
N50LTDK	CN500LTDK	100 ~ 500 #	2.5 #			10 ~ 50 #	0.25	40	200	63							762	No.2, No.3
N100LTDK	N10LTDK	4 ~ 10 N·m	0.05 N·m				45	235	100		11							
N1.5LTDK-H	CN15LTDK-H	1 ~ 15 cN·m	0.1 cN·m				16	111	26	9	10	14.4	35	60	No.0 No.1	Standard bits SB type	Included	
N3LTDK-H	CN30LTDK-H	2 ~ 30 #	0.2 #															

Model (kgf·cm/cN·m)	Range	Increment	Grip Dia.	Total length (without bit)	Dimensions (mm)					Weight	Included Accessory Bits		Extension Bar
	kgf·cm/cN·m		φ mm	mm	L1	L2	φ D1	φ D2	φ D3	g	Phillips	Bit type	
1.5LTDK	0.1~1.5 kgf·cm	0.01 kgf·cm	16	99	14	9	5.5	14.4		50	No.0 No.1	KANON bits OB type	
3LTDK	0.2~3	0.02								190	No.0 No.1		
6LTDK	0.5~6	0.05	25	110	35				20	95	No.0 No.1	Standard bits SB type	Included
12LTDK	2~12	0.1	30						25	190	No.1 No.2		
20LTDK	4~20	0.1	34	157	57		10		34	208	No.2, No.3		
30LTDK	4~30	0.1								436			
50LTDK	10~50	0.25	40	200	73		11			762			
100LTDK	40~100	0.5	45	235	100								
1.5LTDK-H	0.1~1.5	0.01									No.0 No.1		
3LTDK-H	0.2~3	0.02											
N1.5LTDK-H	1~15 cN·m	0.1 cN·m	16	111	26	9	10	14.4	35	60	No.0 No.1		
N3LTDK-H	2~30	0.2											

"-H" models accept standard bits instead of CB type bits.





Bits

Applicable drivers in OB type bits





1.5LTDK, 3LTDK (kgf·cm Unit)

Unit:mm

Phillips	Slot Drive	BOX BITS (Female Hex)	HEX BITS (Male Hex)																																		
																																					
<table><tr><th>φD</th><th>Bit sizes</th></tr><tr><td></td><td>No.00</td></tr><tr><td>3.5φ</td><td>No.0</td></tr><tr><td></td><td>No.1</td></tr><tr><td></td><td>No.2</td></tr></table>	φD	Bit sizes		No.00	3.5φ	No.0		No.1		No.2	<table><tr><th>Blade thickness</th><th>Width</th></tr><tr><td>0.4mm</td><td>3.5mm</td></tr></table>	Blade thickness	Width	0.4mm	3.5mm	<table><tr><th colspan="5">Width across flats</th></tr><tr><td>3</td><td>4</td><td>5</td><td>5.5</td><td>6</td></tr></table>	Width across flats					3	4	5	5.5	6	<table><tr><th colspan="5">Edge size (H) mm</th></tr><tr><td>1.27</td><td>1.5</td><td>2</td><td>2.5</td><td>3</td></tr></table>	Edge size (H) mm					1.27	1.5	2	2.5	3
φD	Bit sizes																																				
	No.00																																				
3.5φ	No.0																																				
	No.1																																				
	No.2																																				
Blade thickness	Width																																				
0.4mm	3.5mm																																				
Width across flats																																					
3	4	5	5.5	6																																	
Edge size (H) mm																																					
1.27	1.5	2	2.5	3																																	

Applicable drivers in CB type bits

CN1.5LTDK, CN30LTDK (N·m Unit)

Phillips	Slot Drive	BOX BITS (Female Hex)	HEX BITS (Male Hex)																																			
																																						
<table><tr><th>ϕD</th><th>Bit sizes</th></tr><tr><td rowspan="4">3.5ϕ</td><td>No.00</td></tr><tr><td>No.0</td></tr><tr><td>No.1</td></tr><tr><td>No.2</td></tr></table>	ϕD	Bit sizes	3.5 ϕ	No.00	No.0	No.1	No.2	<table><tr><th>Blade thickness</th><th>Width</th></tr><tr><td>0.4mm</td><td>3.5mm</td></tr></table>	Blade thickness	Width	0.4mm	3.5mm	<table><tr><th colspan="6">Width across flats</th></tr><tr><td>3</td><td>4</td><td>5</td><td>5.5</td><td>6</td><td></td></tr></table>	Width across flats						3	4	5	5.5	6		<table><tr><th colspan="6">Edge size (H) mm</th></tr><tr><td>1.27</td><td>1.5</td><td>2</td><td>2.5</td><td>3</td><td></td></tr></table>	Edge size (H) mm						1.27	1.5	2	2.5	3	
ϕD	Bit sizes																																					
3.5 ϕ	No.00																																					
	No.0																																					
	No.1																																					
	No.2																																					
Blade thickness	Width																																					
0.4mm	3.5mm																																					
Width across flats																																						
3	4	5	5.5	6																																		
Edge size (H) mm																																						
1.27	1.5	2	2.5	3																																		


Applicable drivers in SB type bits

1.5~3LTDK-H, 6~100LTDK (kgf·cm Unit)

CN15~CN30LTDK-H, CN60~N10LTDK (N·m Unit)


Unit:mm

Phillips




ϕD	Bit sizes
4ϕ	No.0 No.1
7ϕ	No.2 No.3

Slot Drive




Blade thickness	Width
0.4mm	4.0mm
1.0mm	7.0mm

BOX BITS
(Female Hex)



Width across flats					
4	5	5.5	6	7	
8	9	10	11	12	
13	14	17			

HEX BITS
(Male Hex)



Edge size (H) mm					
1.27	1.5	2	2.5	3	
4	5	6	8		

▲ PAGE TOP

HOME
FAQ
News

Corporate Information
Our Brand
Environment and Society
Contact us

Torque apparatus
Torque wrenches
Torque drivers
Torque analyzers
Torque gauges

Vernier Calipers
Calipers
Centerline calipers
Depth Gauges
Hight Gauge

Scope of work in registration: JQA-2434 (ISO9001)
Products: Hand operating torque wrenches, hand operating torque drivers and torque analyzers. Design, development, manufacture and related services (repair, inspection, calibration and supply of service parts) of the above products.



Copyright(C) NAKAMURA Mfg. Co.,Ltd. All Rights Reserved.