

Ohaus® - Scout® SPX Portable Balances - SPX2201

Ohaus® - SPX2201 - Portable Scale

The Ohaus Scout SPX2201 portable balance has a capacity of 2200 grams and a readability of 0.1 grams with a pan size of 5.5 x 6.7 inches. The Scout SPX Gives You An Updated Scout Experience! The new Scout SPX takes everything you love about the Scout Pro, and makes it even better. With a bright LCD display and 4 button control, the Scout SPX brings you efficient operation and ease-of use. Better performance and higher capacities widen the range of weighing applications, while superior overload protection and impact-resistant pan support bring you the peace of mind you rely on from OHAUS.



81

Are you a scale reseller? Call us for resale pricing or send your inquiry to resale@affordablescales.com

Special Features:

- Combined with a simplified 4 button operation, the Scout's large backlit display increases readability in low light working conditions, and is easier to view from a distance.
- Integrated superior overload protection and impact-resistant pan support safeguard against shock and overloading the balance in rugged and demanding environments.
- Stabilization time as fast as 1 sec and advanced weighing technology, lead to improved productivity in your facility. Increased capacity unlocks a wider range of weighing applications.
- RS232, USB Host, USB Device, Ethernet or Bluetooth (available as accessories)
- **2 Year Warranty**

YOUR PRICE: \$297.00

FREE SHIPPING

Free UPS Ground shipping within the 48 contiguous United States.

Specifications:

Ohaus - SPX2201	
Capacity	2200 g
Readability	0.1 g
Pan Size	5.5 x 6.7" / 140 mm x 170 mm
Repeatability (Std. Dev.)	0.1 g
Linearity	0.1 g
Span Calibration Mass	2 kg
Linearity Calibration Masses	1, 2 kg
Stabilization Time	1 second
Construction	ABS housing & stainless steel pan
Calibration	User-selectable external span or linearity calibration / Digital with external weight
Tare Range	Full capacity by subtraction
Weighing Units	g, kg, ct, N, oz, ozt, dwt, lb, lb:oz, grn, hkt, sgt, twt, tical, tola
Application Modes	Weighing, Parts Counting, Percent Weighing, Check Weighing, Totalization, Display Hold
Power	Standard AC Power Adapter – 5VDC 1A output, or 4 AA dry battery (not included)
Typical Battery Life	80 hours
Interfaces	RS232 (Optional), USB Device (Optional), Ethernet (Optional), Bluetooth (Optional), USB Host (Optional)
Display Type	Full-Color Touchscreen WQVGA Graphic LCD
Overload Capacity	10 times rated capacity
Operating Temperature Range	50° - 104°F / 10° - 40°C 10% to 85% at 31°C, decreasing linearly to 50% at 40°C, non-condensing
Storage Conditions	-4° - 131°F / -20° - 55°C at 10% to 90% relative humidity, non-condensing
Dimensions (W x D x H)	8 x 8.8 x 2.1 in / 202 x 224 x 54 mm
Shipping Dimensions (W x D x H) / Weight	11.8 x 9.8 x 3.4 in / 3.5 lbs

Accessories for SPX2201: **To order Accessories please call**

Item No	Accessory	Your Price
30064203	SF40A Impact Printer	\$867.60
30268982	RS232 Kit	\$145.80
30268983	USB Kit, Host (Scale to USB Drive)	\$145.80
30268984	USB Kit, Device (Scale to Computer)	\$101.70
30268985	Bluetooth Kit	\$131.40
30268986	Ethernet Kit	\$158.40
30268987	Stacking Kit/Storage Cover, pack of 6	\$57.60
30268988	Stacking Kit/Storage Cover	\$19.80
30269019	Auxiliary Display Kit	\$132.30
80850043	Anti-Theft Device	\$203.40
30269022	In-use Cover, Scout	\$19.80
30269021	Carrying Case, Scout	\$114.30

Thank you!