



PIC GAUGES

Industrial Pressure Gauge: 0 to 1,000 psi, 4 in Dial, Liquid-Filled, 1/2 in NPT Male

Item #20TV78 Mfr. Model 201L-402M
UNSPSC #23151820 Catalog Group #H8403
Catalog Page #568

Country of Origin China. Country of Origin is subject to change.

Web Price
\$52.95 / each

Qty1

Add to Cart

☒ Ship

☐ Pickup

Expected to arrive Mon. Aug 29.

Ship to 78613 | [Change](#)

Shipping Weight 1.75 lbs

[Ship Availability Terms](#)

Add to List

Technical Specs

Item	Industrial Pressure Gauge	Primary Pressure Range	0 to 1,000
Nominal Dial Size	4 in	Dry Dampening Feature	None
Accuracy	+/-1.0%	Vibration Resistance	Liquid-Filled
Gauge Case Material	Stainless Steel	Dial Color	White
Process Connection Type	NPT	Pressure Gauge Type	Industrial Pressure Gauge
Process Connection Gender	Male	Liquid-Filled Case	Yes
Lens Material	Polycarbonate	Gauge Case Liquid	Glycerin
Process Connection Size	1/2 in	Panel-Mountable	No
Field Fillable	No	Socket Material	Copper Alloy
Process Connection Location	Bottom	Sensor Material	Copper Alloy
Case Color	Metallic	Accuracy Grade	ASME B40.100 Grade 1A
		Series	201L

IP/NEMA Rating	Not Rated	Application	General Purpose
Primary Scale Units	psi	Includes Mounting Hardware	No
Accuracy Scale	Full Scale	Includes Vent Plug	Yes
Ambient Operating Temperature Range	30 Degrees to 160 Degrees F	Manufacturer Warranty Length	1 yr
Bezel Material	Stainless Steel	Mounting Type	Stem-Mount
Bezel Mounting Type	Fixed	Non-Sparking	No
Blowout Safety Back	No	Pointer Color	Black
Case Depth	1.75 in	Pointer Material	Aluminum
Case Diameter	4.29 in	Pressure Range Type	Pressure
Cleaned for Oxygen Service	No	Primary Scale Minor Graduations	20
Dial Face Material	Aluminum	Removable Bezel	No
Freeze Resistant Movement	No	Scale Type	Dual
Hazardous Location Rating	Not Rated	Secondary Pressure Range	0 to 69
Includes	Vent Plug	Secondary Scale Units	bar
Includes Calibration Certificate	No	Standards	ASME

Compliance and Restrictions

 WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov