

▲ [See All Proto® Dial Torque Wrenches - In-Lbs/Cm Kg](#)



PROTO® 3/8" DRIVE DIAL TORQUE WRENCH 50-250 IN-LBS, 56-280 CM KG

ITEM #J6177F

Features and benefits

- 6-30 in-lbs thru 120-600 in-lbs / 7-35 cm kg thru 140-700 cm kg.
- Accurate to $\pm 4\%$ of torque reading in both directions at 20% to 100% of full scale.
- Industrial all steel or aluminum torque transfer components.
- High alloy torsion drive design — accuracy not effected by hand position.
- Dual scale (English/Metric) with clockwise and counterclockwise operation — fewer wrenches needed to complete job.
- Memory needles are standard on all wrenches except electric light models.
- Easy-to-read, high contrast scale.
- Laser marked serial number for traceability.
- N.I.S.T. (National Institute of Standards and Technology) traceable CW certification supplied with each wrench.

Specifications

DRIVE SIZE [IN]	3/8
INCREMENTS [IN LBS]	5
TORQUE RANGE [IN LBS]	50-250
TORQUE RANGE	56-280 cm kg
OVERALL LENGTH [IN]	10
WEIGHT [LBS]	1.30
FINISH	Full Polish
SPECIFICATION ASME	ASME B107.14M
SPECIFICATION ISO	ISO 6789
SPECIFICATION_JIS	JIS B4650