

Klutch 1/2in.-Drive Mechanical Torque Wrench — 30–250 Ft./Lbs.

Key Specs

Attribute	Specification
Item#	49326
Brand	Klutch
Tool Length	24 in
Attribute	Specification
Measurement Standard	Standard (SAE)
Torque Range	250 ft-lbs.
Reversible	Yes
Accuracy	0.03



Product Summary

The Klutch® 1/2in.-Drive Mechanical Torque Wrench offers a 30–250 ft./lbs. torque range and is accurate to $\pm 3\%$. Also features a locking ring, reverse lever and 32-tooth gearing with a 11° ratcheting arc. Meets or exceeds ASME B107.300-2010.

Features + Benefits

- Torque range: 30–250 ft./lbs.
- 1/2in. drive
- Thin profile, high-strength teardrop head for easy access
- 1-finger operated reverse lever
- 32-tooth ratchet with 11° ratcheting arc
- Sealed ratchet head design guards against dirt infiltration
- Micrometer locking ring provides secure locking mechanism
- Accurate in clockwise direction to $\pm 3\%$ in upper 80% of range
- Meets or exceeds ASME B107.300-2010
- Note: torque wrench should be checked for accuracy periodically, at least once a year or every 10,000 torque application cycles, whichever comes first, or after any abnormal handling

<https://www.northerntool.com/products/klutch-1-2in-drive-mechanical-torque-wrench-30-250-ft-lbs-49326>