



Vertical Torque Gauges / Vertical Torque Screwdrivers

The Seekonk Vertical Torque gauges are designed for low torque range tightening in inch grams, inch ounces, and inch pounds; these versatile and dependable tools feature precision thrust and lateral bearings which insure accuracy to within +/- 3%. Ideal for use in electronics, medical, communications, aircraft and automotive industries. Dials designed to minimize parallax error.

Model #	Torque Range	Dial Graduation	Directions
GS-170	0-170 in. gr.	10 in. gr.	Both left and right
GS-350	0-350 in. gr.	25 in. gr.	Both left and right
S0-12	0-12 in. ozs.	.50 in. ozs.	Both left and right
S0-24	0-24 in. ozs.	1 in. ozs.	Both left and right
S0-3	0-3 in. ozs.	.25 in. ozs.	Both left and right
S0-48	0-48 in. ozs.	2 in. ozs.	Both left and right
S0-6	0-6 in. ozs.	.50 in. ozs.	Both left and right
S0-96	0-96 in. ozs.	4 in. ozs.	Both left and right
SL-100 Left	0-100 in. lbs.	5 in. lbs.	Left Only
SL-100 Right	0-100 in. lbs.	5 in. lbs.	Right Only
SL-12	0-12 in. lbs.	.50 in. lbs.	Both left and right
SL-25 Left	0-25 in. lbs.	1 in. lbs.	Left Only
SL-25 Right	0-25 in. lbs.	1 in. lbs.	Right Only
SL-50 Left	0-50 in. lbs.	2 in. lbs.	Left Only
SL-50 Right	0-50 in. lbs.	2 in. lbs.	Right Only
SL-6	0-6 in. lbs.	.25 in. lbs.	Both left and right
SL-80 Left	0-80 in. lbs.	5 in. lbs.	Left Only
SL-80 Right	0-80 in. lbs.	5 in. lbs.	Right Only

<https://www.seekonk.com/cat-44-1-31/vertical-torque-gauges.htm>