

AMP (NS)	4-COND,6-PIN
PIN	DESIGNATION
A	(+) SUPPLY
B	SUPPLY RETURN
C	(-) OUTPUT
D	(+) OUTPUT
E	N/C
F	N/C

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.
PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL.
THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS										INITIAL RELEASE TO PRODUCTION		—		—		—			
REV		DESCRIPTION		MFG:		XX/XX/XX		ENG:		VICARS		CHK		APV		BY			
DRW:		4/30/2003		CHK:		5/2/2003		VICARS		5/2/2003		MFG:		XX/XX/XX		05/09/2006			
Honeywell										HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing									
DATABASE VERIFIED:										EXTERNAL WIRING CODE									
PLOT FILE VERIFIED:										AMP (NS) 6PIN, 4-COND									
CATALOG VERIFIED:										DOCUMENT NUMBER									
CATALOG REFERENCE:										001-0686-00									