



PRE-SET "L" HANDLE SLIP TYPE TORQUE WRENCHES

Seekonk "L" handle slip type torque tools extend fool proof versatility into a convenient "low profile" configuration. As with our other slip type tools, over torquing is impossible even with continued turning. Minimum head diameter design allows access into hard to reach areas. The unmatched performance and endurance exhibited by these tools are made possible by internal components produced on Seekonk's state of the art CNC machining centers. Both the advanced design and production of these and all other Seekonk products are controlled by our ISO 9001 quality system.

Tools are pre-set at the factory to your requirements. Under normal use, yearly calibration is sufficient, however; routine calibration checks on a Seekonk Analog or PDTs electronic torque analyzer would be considered prudent. **Standard accuracy +/- 4%.**

All tools are manufactured in Massachusetts and are shipped with complementary NIST certs.

MODEL #	TORQUE RANGE	DRIVE	LENGTH	HEIGHT	WEIGHT
<u>LT-M</u>	2-20 in. lbs.	1/4"	4 1/2"	1 3/8"	6 oz.
<u>LT-O</u>	5-60 in. lbs.	3/8"	6 1/8"	1 5/8"	13 oz.
<u>LT-L</u>	5-60 in. lbs.	3/8"	6 1/8"	1 5/8"	13 oz.
<u>LT-R 1/4</u>	30-100 in. lbs.	1/4"	7"	3 1/4"	4 oz.

<u>LT-R 3/8</u>	30-100 in. lbs.	3/8"	7"	3 1/4"	4 oz.
<u>MR-1</u>	3-15 ft. lbs.	1/2"	9 5/8"	2 3/8"	35 oz.
<u>MR-1D 3/8</u>	3-15 ft. lbs.	3/8"	9 5/8"	2 3/8"	35 oz.
<u>MR-1D 1/2</u>	3-15 ft. lbs.	1/2"	9 5/8"	2 3/8"	35 oz.
<u>MR-1L 3/8</u>	3-15 ft. lbs.	3/8"	9 5/8"	2 3/8"	35 oz.
<u>MR-1L 1/2</u>	3-15 ft. lbs.	1/2"	9 5/8"	2 3/8"	35 oz.
<u>MR-2 3/8</u>	15-30 ft. lbs.	3/8"	9 5/8"	2 3/8"	35 oz.
<u>MR-2 1/2</u>	15-30 ft. lbs.	1/2"	9 5/8"	2 3/8"	35 oz.
<u>MR-2D 3/8</u>	15-30 ft. lbs.	3/8"	9 5/8"	2 3/8"	35 oz.
<u>MR-2D 1/2</u>	15-30 ft. lbs.	1/2"	9 5/8"	2 3/8"	35 oz.
<u>MR-2L 3/8</u>	15-30 ft. lbs.	3/8"	9 5/8"	2 3/8"	35 oz.
<u>MR-2L 1/2</u>	15-30 ft. lbs.	1/2"	9 5/8"	2 3/8"	35 oz.
<u>MR-3</u>	30-90 ft. lbs.	1/2"	17"	2 1/2"	55 oz.

<https://www.seekonk.com/cat-40-1-28/pre-set-l-handle-slip-type-torque-wrenches.htm>