



PIC GAUGES

Industrial Pressure Gauge: 0 to 600 psi, 4 in Dial, Liquid-Filled, 1/2 in NPT Male, 300

Item #30ZV88 Mfr. PRO-301L- Model # 402K-01
UNSPSC #23151820 Catalog Group #H8407
Catalog Page #568

Country of Origin India. Country of Origin is subject to change.

Web Price
\$93.82 / each

Qty
1

Add to Cart

☒ Ship

☐ Pickup

Expected to arrive Mon. Aug 29.

Ship to 78613 | Change

Shipping Weight 1.7 lbs

[Ship Availability Terms](#)

Add to List

Technical Specs

Item	Industrial Pressure Gauge
Nominal Dial Size	4 in
Accuracy	+/-2-1-2%
Gauge Case Material	Stainless Steel
Process Connection Type	NPT
Process Connection Gender	Male
Lens Material	Polycarbonate
Process Connection Size	1/2 in
Field Fillable	No
Process Connection Location	Bottom
Case Color	Metallic

Primary Pressure Range	0 to 600
Dry Dampening Feature	None
Vibration Resistance	Liquid-Filled
Dial Color	White
Pressure Gauge Type	Industrial Pressure Gauge
Liquid-Filled Case	Yes
Gauge Case Liquid	Glycerin
Panel-Mountable	No
Socket Material	316 Stainless Steel
Sensor Material	316 Stainless Steel
Accuracy Grade	ASME B40.100 Grade A

IP/NEMA Rating	Not Rated	Series	300
Application	Industrial	Includes Vent Plug	No
Primary Scale Units	psi	Manufacturer Warranty Length	1 yr
Accuracy Scale	Mid-Scale	Mounting Type	Stem-Mount
Ambient Operating Temperature Range	30 Degrees to 160 Degrees F	Non-Sparking	No
Bezel Material	Stainless Steel	Pointer Color	Black
Bezel Mounting Type	Fixed	Pointer Material	Aluminum
Blowout Safety Back	No	Pressure Range Type	Pressure
Case Depth	1.74 in	Primary Scale Minor Graduations	10
Case Diameter	4.3 in	Primary Scale Numeric Increments	100
Cleaned for Oxygen Service	No	Removable Bezel	No
Dial Face Material	Stainless Steel	Scale Type	Dual
Freeze Resistant Movement	No	Secondary Pressure Range	0 to 41
Hazardous Location Rating	Not Rated	Secondary Scale Units	bar
Includes Calibration Certificate	No	Standards	ASME
Includes Mounting Hardware	No		