



Digital Indicator ID-C, ASME/ANSI Type

Item number: 543-732B

Images



Description

This is a multifunction standard indicator that is reliable and easy to use.

- Bidirectional communication e.g. to perform parameter setting from a PC (Digimatic S 1 interface) is possible.
- The ABSOLUTE sensor means you don't have to carry out origin setting every time you power it on, saving you time and hassle.
- Excellent visibility with a large digital/analog display.
- Model with 0,5 μm digital step is available.
- Measurements such as simple calculation and peak detection are possible.
- Equipped with a calibration schedule warning function.
- GO/ $\pm$ NG judgement is performed by setting the upper and lower tolerances.
- Display 330° rotatable.
- A function lock protects the display against unauthorised use.

Features

Digital/Analog:	Digital
Inch-Metric:	Inch/Metric
Delivered:	Including CR2032 battery, battery lid opener, lifting handle, certificate of inspection
Range:	2"/50.8 mm
Digital step:	0.00002"/0.00005"/0.0001"/0.0005" 0.0005 mm/0.001 mm/0.01 mm
Max. Permissible Error E MPE (Total Range):	±0.00020"/0.005 mm
H MPE (Hysteresis):	0.00008"/0.002 mm
R MPE (Repeatability):	0.00008"/0.002 mm
Measuring force MPL:	≤2.3 N
Protection:	IP42
Type:	ASME/ANSI/AGD Standard
Mass:	260 g
Display:	LCD, character height 11 mm, 330° rotatable
Max. response speed:	Unlimited
Measurement frequency (MAX/MIN/RANGE):	50 times/s
Alarm:	Low voltage, setting errors, sensor error, display overflow a.s.o.
Stem Ø:	9.52 mm
Contact point:	Carbide ball, thread: No.4-48UNF
Power supply:	1 battery CR2032
Battery life:	Approx. 2700 hours (continuous use)
DATA/HOLD:	Yes
Digimatic data output:	Yes
Digimatic S1 Bidirectional interface:	Yes
ON/OFF:	Yes
Analog bar resolution switchable:	Yes
Function lock:	Yes
GO/±NG judgement:	Yes
ABS / INC (INC ZERO):	Yes
Analog bar resolution selection:	Yes

Auto Power OFF setting:	Yes
Calculation function (with formula):	Yes
Customizing keys:	Yes
Counting direction switchable:	Yes
Inch/Metric switchable:	Yes
Calibration warning function:	Yes
Digital step switchable:	Yes
Delivered:	Including CR-2032 battery, battery lid opener, spindle lifting handle (25,4 and 50,8 mm models), weight (low force models), certificate of inspection
Digital Scale:	Electrostatic capacitance type absolute linear encoder

Dimensions

Accessories

Optional accessories:



Digimatic Cable, Straight, 1m

Digimatic/Digimatic 2/Digimatic S1 Interface
Art No. 06AGL011
Suggested retail price: **79.00 €***



Digimatic Cable, Straight, 2m

Digimatic/Digimatic 2/Digimatic S1 Interface
Art No. 06AGL021
Suggested retail price: **84.00 €***



USB Input Tool Direct (Digimatic to USB)

2m Cable, Digimatic/Digimatic 2/Digimatic S1
Interface

Art No. 06AGQ001F

Suggested retail price: **164.00 €***



USB Input Tool Interface Box

Digimatic/Digimatic 2/Digimatic S1 Interface

Art No. 264-020

Suggested retail price: **259.00 €***



U-WAVE fit, Buzzer Type

Wireless Transmitter for
Micrometer/Indicator

Art No. 264-623

Suggested retail price: **185.00 €***



U-WAVE fit, IP67 Type

Wireless Transmitter for
Micrometer/Indicator

Art No. 264-622

Suggested retail price: **185.00 €***



U-WAVE fit Bluetooth, Buzzer Type

Wireless Transmitter for
Micrometer/Indicator

Art No. 264-627

Suggested retail price: **185.00 €***



U-WAVE fit Bluetooth, IP67 Type

Wireless Transmitter for
Micrometer/Indicator

Art No. 264-626

Suggested retail price: **185.00 €***



Connection Cable SF for U-WAVE

for U-WAVE-T and Instruments with
Digimatic S1 Interface

Art No. 02AZG011

Suggested retail price: **131.00 €***



U-WAVE fit Transmitter Mounting Plate

for ID-C, ID-S and ID-F Digital Indicator

Art No. 02AZF670

Suggested retail price: **47.00 €***



Spindle Lifting Knob

for 50,8mm Range
Art No. 21EZA200
Suggested retail price: **89.00 €***

Mitutoyo

MICAT
the standard in world
metrology software
MeasurLink

USB-ITPAK Vers. 3.0

USB Dongle + Manual (Software available
Online)
Art No. 06AGR543
Suggested retail price: **340.00 €***



Standard accessories:

Battery Case Opener

Art No. 21EAB049
Suggested retail price: **0.80 €***



Spare parts

Consumable spares:



Lithium battery CR-2032

1 pcs.

Art No. 05SAA217D

Suggested retail price: **10.00 €***