



Eastern Pneumatics & Hydraulics, Inc.

EPH EASTERN PNEUMATICS & HYDRAULICS, INC.

Eastern Pneumatics & Hydraulics, Inc.

☎ USA T. +1.800.356.5624


www.ephtools.com | info@ephtools.com

McCann Equipment Ltd.

☎ CAN T. +1.800.663.6344

www.torquetools.com | info@torquetools.com

Hours: Monday to Friday: 8:00 am - 4:30 pm | Saturday & Sunday: Closed



Industries

TIREMAN II – TM600 / TM750

USE / APPLICATION

Wheelbolt Tightening

PRODUCT TYPE

Torque Wrench

MODEL

TM600 / TM6001 and TM750 / TM7501

RANGE

TM600 (3/4" Standard)/TM6001 (1" Optional) 200-800 N·m (150-600 lbf·ft)/TM750 (3/4" Standard) / TM7501(1" Optional) 300-1,000 N·m (200-750 lbf·ft)

INDUSTRIAL STRENGTH

BREKBACK TORQUE WRENCH®

- Accurate results, to $\pm 4\%$, even in harsh conditions.
- The wrenches are accompanied by a calibration certificate satisfying ISO 17025 requirements.
- Accurately torques both right and left handed threads
- The break back action can be seen and felt
- Improved accuracy with the break angle reducing the possibility of over torquing
- Equally at home in the garage or on the service truck
- Dual scale, N.m and lbf.ft

TM600 – Square Drive 3/4" – Range 200-800 N·m (150-600 lbf·ft)

TM6001 – Square Drive 1" – Range 200-800 N·m (150-600 lbf·ft)

TM750 – Square Drive 3/4" – Range 300-1,000 N·m (200-750 lbf·ft)

TM7501 – Square Drive 1" – Range 300-1,000 N·m (200-750 lbf·ft)

NOTE: Specifications & design / subject to change without notice.
Color may differ from that shown.

*** TIREMAN II TORQUE WRENCH™ is a trademark of: Eastern Pneumatics & Hydraulics, Inc.**

*Specifications / design / accessories / options / features
are subject to change without notice.
Color may differ from image shown.