



Blog



Videos

- FAQs
- Glossary
- Newsletters

- About
- Contact



Mitutoyo > Indicators > Mitutoyo 2776A Dial Indicator Standard Type 0-1"



MITUTOYO 2776A DIAL INDICATOR STANDARD TYPE 0-1"

Product Code: 2776A

MFGID: 2776A

Brand: Mitutoyo

Range: 0-1"

Graduations: .0005"

Back Type: Lug



Authorized Distributor

Select A Size Option

2776A

~~\$167.00~~ **\$143.62**

Lowest Price Guaranteed

Quantity

-

1

+



ADD TO CART

Product Description

2776A Mitutoyo Series 2 Dial Indicator Standard Type: 0-1"

The Mitutoyo **2776A** Series 2 Standard Type Dial Indicator has the following specifications:

- Range: 0-1"
- Graduation: .0005"
- Range/Rev: .05"
- Dial Reading: 0-50
- Type: lug back
- Accuracy (First 2.5 Rev): +/- .0005"
- Accuracy (Overall): +/- .002"
- Measuring force: 2.5N or less
- Stem/Shank: 3/8"
- Contact Point: #4-48 UNF Thread
- Shockproof Type: No
- Reverse Reading Type: No
- Jeweled Bearing Type: No
- Type: ANSI/AGD

The Mitutoyo inch reading dial indicator performs with excellent accuracy and reliability, and it is available in several graduations and ranges for use in the widest range of applications. The 2776A stem and spindle are constructed of hardened, high-strength steel, and the jeweled bearing provides wear resistance and low friction movements for smooth, precise operations. Secured adhesion between the frame and crystal, along with the use of an O-ring, protects the indicator against water and oil permeation via the front face. The crystal has a scratch and glare-resistant coating for clearer readings and better durability. The outer clamp and optional lifting lever can be attached to either side and can be easily installed or removed without the use of tools. The [Mitutoyo Series 2 standard diameter dial indicator](#) with inch reading offers simplicity, accuracy and durability for any application, making it our most popular indicator. This indicator conforms to ANSI/AGD Standards.