



Dial Indicator, Lug Back, AGD/ANSI
0,05", 0,0001", Jew. Bearing, Shockproof
Item number: 2923S-10



Description

Standard Type, Various Ranges, 0,0001" Graduation - Inch

- This is a standard, inch dial indicator. It offers you the following benefits:
- Bezel clamp and lifting lever (optional) can be attached to either right or left side. They can be easily installed and removed without tools.
 - No through screw holes on the frame and secure adhesion between the bezel and the crystal as well as the use of an O-ring prevents water or oil penetration.

Features

Range:	0,05"
Range per rev.:	0.01"
Scale:	0-5-0

Accuracy:	±0,0002"
Mass:	164 g
Type:	ANSI/AGD Standard
C:	57 mm
D:	17.7 mm
E:	19 mm
F:	13.6 mm
G:	9.6 mm
I:	7.6 mm
Digital/Analog:	Analog
Inch-Metric:	Inch
Error of indication one revolution:	±0,0002"
Stem:	9.52 mm / 0.375"
Contact point:	Carbide tipped, thread: 4-48UNF
Delivered:	with certificate of inspection, limit indicators
Balanced dial:	Yes
Continuous dial:	Yes
Reverse reading:	Yes 3
Shockproof:	Yes
Jeweled Bearing:	Yes
Functions:	ANSI/AGD type

Dimensions



**Consumable spares:**