



PM500 Pressure Measurement Modules

For [2271A Industrial Pressure Calibrator](#) ([/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-0](#)) and [6270A](#) ([/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-1](#)), [8270A](#) and [8370A](#) ([/products/pressure-calibration/automated-pressure-controller-calibrators/high-pressure-pneumatic-co-1](#)) Pressure Controller / Calibrators



(https://us.flukecal.com/sites/default/files/imagecache/product-detail-zoom/sites/flukecal.com/files/assets/accessories/Fc-pm500-bg20m_01a_c.jpg)

Highlights ([/products/accessories/gauge-pressure-modules/pm500-pressure-measurement-modules?quicktabs_accessory_details=0#quicktabs_accessory_details](#))

Specifications ([/products/accessories/gauge-pressure-modules/pm500-pressure-measurement-modules?quicktabs_accessory_details=2#quicktabs_accessory_details](#))

Performance specifications

The performance specifications describe the complete instrumental uncertainty of the Product. The specifications include all relevant error components (linearity, hysteresis, repeatability, resolution, reference standard measurement uncertainty, 1-year drift, and temperature effects). The specifications are provided at a level of confidence of 95 %, k=2, normally distributed. Precision uncertainty includes linearity, hysteresis, repeatability, resolution, and temperature effects.

PM500 Modules measurement specifications

Specifications are valid from 15 °C to 35 °C.

Model	Range (SI Units)	Range (Imperial Units)	Measurement Mode ²	1-Year Instrumental Uncertainty (% of reading or % FS, whichever is greater) unless otherwise stated	1-Year Zero Instrumental Drift % FS, RSS with 1-Year Instrumental Uncertainty ¹	Precision Uncertainty (% of reading or % FS, whichever is greater)
PM500-G100K ⁴	0 kPa to 100 kPa	0 psi to 15 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G200K ⁴	0 kPa to 200 kPa	0 psi to 30 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G250K ⁴	0 kPa to 250 kPa	0 psi to 36 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G350K ⁴	0 kPa to 350 kPa	0 psi to 50 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G400K ⁴	0 kPa to 400 kPa	0 psi to 60 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G600K ⁴	0 kPa to 600 kPa	0 psi to 90 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035

PM500-G700K ⁵	0 kPa to 700 kPa	0 psi to 100 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG1M ⁵	-0.1 MPa to 1 MPa	-15 psi to 150 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG1.4M ⁵	-0.1 MPa to 1.4 MPa	-15 psi to 200 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG2M ⁵	-0.1 MPa to 2 MPa	-15 psi to 300 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG2.5M ⁵	-0.1 MPa to 2.5 MPa	-15 psi to 400 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG3.5M ⁵	-0.1 MPa to 3.5 MPa	-15 psi to 500 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG4M ⁵	-0.1 MPa to 4 MPa	-15 psi to 600 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG7M ⁵	-0.1 MPa to 7 MPa	-15 psi to 1000 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG10M ⁵	-0.1 MPa to 10 MPa	-15 psi to 1500 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG14M ⁵	-0.1 MPa to 14 MPa	-15 psi to 2000 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG20M ⁵	-0.1 MPa to 20 MPa	-15 psi to 3000 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BA120K ^{3,6}	60 kPa to 120 kPa	8 psi to 17 psi	absolute	0.01 % of reading	0.05	0.005 % of reading
PM500-A120K ^{3,6}	0.08 kPa to 120 kPa	0.01 psi to 16 psi	absolute	0.01 or 0.005	0.05	0.007 or 0.0035
PM500-A160K ^{3,6}	0.08 kPa to 160 kPa	0.01 psi to 23 psi	absolute	0.01 or 0.005	0.05	0.007 or 0.0035
PM500-A200K ^{3,4}	0.08 kPa to 200 kPa	0.01 psi to 30 psi	absolute	0.01 or 0.005	0.05	0.007 or 0.0035
PM500-A350K ⁴	0.08 kPa to 350 kPa	0.01 psi to 50 psi	absolute	0.01 or 0.005	0.03	0.007 or 0.0035
PM500-A700K ⁴	0.08 kPa to 700 kPa	0.01 psi to 100 psi	absolute	0.01 or 0.005	0.025	0.007 or 0.0035
PM500-A1.4M ⁵	0.035 MPa to 1.4 MPa	5 psi to 200 psi	absolute	0.01 or 0.005	0.015	0.007 or 0.0035
PM500-A2M ⁵	0.07 MPa to 2 MPa	10 psi to 300 psi	absolute	0.01 or 0.005	0.015	0.007 or 0.0035
				(% FS + % of reading)		(% FS + % of reading)
PM500-G2.5K ⁶	0 kPa to 2.5 kPa	0 inH ₂ O to 10 inH ₂ O	gauge	0.03 + 0.02	-	0.015 + 0.01
PM500-G7K ⁶	0 kPa to 7 kPa	0 inH ₂ O to 30 inH ₂ O	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G14K ⁶	0 kPa to 14 kPa	0 inH ₂ O to 50 inH ₂ O	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G20K ⁶	0 kPa to 20 kPa	0 inH ₂ O to 80 inH ₂ O	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G35K ⁶	0 kPa to 35 kPa	0 psi to 5 psi	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G70K ⁶	0 kPa to 70 kPa	0 psi to 10 psi	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-NG100K ⁶	-100 kPa to 0 kPa	-15 psi to 0 psi	negative gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG1.4K ⁶	-1.4 kPa to 1.4 kPa	-5 inH ₂ O to 5 inH ₂ O	bi-directional gauge	0.03 + 0.02	-	0.015 + 0.01
PM500-BG2.5K ⁶	-2.5 kPa to 2.5 kPa	-10 inH ₂ O to 10 inH ₂ O	bi-directional gauge	0.03 + 0.02	-	0.015 + 0.01

PM500-BG3.5K ⁶	-3.5 kPa to 3.5 kPa	-15 inH ₂ O to 15 inH ₂ O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG7K ⁶	-7 kPa to 7 kPa	-30 inH ₂ O to 30 inH ₂ O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG14K ⁶	-14 kPa to 14 kPa	-50 inH ₂ O to 50 inH ₂ O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG25K ⁶	-25 kPa to 25 kPa	-100 inH ₂ O to 100 inH ₂ O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG40K ⁶	-40 kPa to 40 kPa	-6 psi to 6 psi	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG60K ⁶	-60 kPa to 60 kPa	-9 psi to 9 psi	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
				% FS		% FS
PM500-BG100K ⁴	-100 kPa to 100 kPa	-15 psi to 15 psi	bi-directional gauge	0.01	-	0.005
PM500-BG200K ⁴	-100 kPa to 200 kPa	-15 psi to 30 psi	bi-directional gauge	0.01	-	0.005
PM500-BG250K ⁴	-100 kPa to 250 kPa	-15 psi to 36 psi	bi-directional gauge	0.01	-	0.005
PM500-BG350K ⁴	-100 kPa to 350 kPa	-15 psi to 50 psi	bi-directional gauge	0.01	-	0.005
PM500-BG400K ⁴	-100 kPa to 400 kPa	-15 psi to 60 psi	bi-directional gauge	0.01	-	0.005
PM500-BG700K ⁵	-100 kPa to 700 kPa	-15 psi to 100 psi	bi-directional gauge	0.01	-	0.005

Notes

1. The 1 Year Instrumental Uncertainty is specified with a zeroing technique in the Operators Manual. If not adhered to the 1 Year Instrumental Uncertainty is:

$$\sqrt{\left(\frac{1 \text{ year instrumental uncertainty}}{2}\right)^2 + \left(\frac{1 \text{ year zero drift}}{1.73}\right)^2} \times 2$$

2. PM500 gauge or bi-directional mode modules support absolute mode measurement when used with a Barometric Reference Module. Instrumental uncertainty for gauge mode modules used in absolute mode by addition of a barometric reference module is calculated as the uncertainty of the gauge mode module root sum squared with the uncertainty of the barometric reference module. Uncertainty for gauge mode assumes routine zeroing which is default operation mode when used in a chassis.
3. These modules can be used as barometric reference modules on all chassis.
4. Compatible with [2271A \(/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-0\)](#), [6270A \(/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-1\)](#) and [8270A \(/products/pressure-calibration/automated-pressure-controller-calibrators/high-pressure-pneumatic-co-1\)](#)
5. Compatible with [2271A \(/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-0\)](#), [6270A \(/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-1\)](#), [8270A and 8370A \(/products/pressure-calibration/automated-pressure-controller-calibrators/high-pressure-pneumatic-co-1\)](#)
6. Compatible with [2271A \(/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-0\)](#) and [6270A \(/products/pressure-calibration/automated-pressure-controller-calibrators/pneumatic-pressure-control-1\)](#)