

120^{XP} Micrometer Torque Wrenches

- Accurate in clockwise direction +/- 3% from 20% to 100% of full scale


- Meets or exceeds ASME B107.300

- Enclosed head design for extreme resistance to dirt infiltration

- Teardrop low profile head and flush mounted on/off switch allow better access in tight spaces

- Pull back locking collar

- Injection molded cases with removable lids for convenient storage



- Double-stacked pawls engage a 60-tooth gear providing exceptional strength, exceeding ASME specifications

- 120 positions, 3 degree ratcheting arc



85181
1/2" Drive



- High definition scale markings are easier to read

- Dual Scales, Metric and SAE

- Pull back locking collar



- Knurled aluminum grip
- Midpoint marked for accuracy

PRECISION FOR
+/- 3%
TORQUE ACCURACY

3° SWING ARC
120^{XP}
FOR TIGHTER TURNS

LOW PROFILE HEAD
FLUSH REVERSING LEVER

FLEX HEAD
FOR ACCESS

THIN PROFILE
FOR ACCESS

Cat. No.	Certified Model No.	Drive Size	Head Style	Primary Scale Range	Primary Scale Increments	Alt. Scale Range	Alt Scale Increments	Tooth Count	Head Thickness (in)	Head Width (in)	Overall Length (in)	Product Weight
85171	85171CERT	1/4"	Standard	30-200 in/lbs	1 in/lb	4 - 23 Nm	0.11 Nm	60T/120 Pos.	0.39	1	11	0.85
85176	85176CERT	3/8"	Standard	10-100 ft/lbs	1 ft/lb	20 - 142 Nm	14 Nm	60T/120 Pos.	0.55	1.25	18.35	2.55
85181	85181CERT	1/2"	Standard	30-250 ft/lbs	2 ft/lb	54 - 353 Nm	2.7 Nm	60T/120 Pos.	0.75	1.75	24.875	3.7
85174	85174CERT	3/8"	Standard	30 - 250 in/lbs	1 in/lb	4 - 23 Nm	0.11 Nm	60T/120 Pos.	0.55	1.25	18.25	2.55
85180	85180CERT	1/2"	Standard	20 - 150 ft/lbs	1 ft/lb	27 - 203 Nm	14 Nm	60T/120 Pos.	0.75	1.75	24.88	3.7
85188	85188CERT	3/8"	Flex	5-75 ft/lbs	1 ft/lb	7 - 136 Nm	14 Nm	60T/120 Pos.	0.55	1.25	18.5	2.6
85189	85189CERT	1/2"	Flex	30-250 ft/lbs	2 ft/lb	54 - 353 Nm	2.7 Nm	60T/120 Pos.	0.75	1.75	26	4