

JAMESON/ITL

Insulated Torque Wrench, Foot-Pound, Newton-Meter, Drive Size 3/8 in



Item #60TA33 Mfr. Model JT-ST-# 01711
UNSPSC #27111715 Catalog Page #N/A

Country of Origin United Kingdom. Country of Origin is subject to change.

Insulated micrometer torque wrenches have a cushioned grip to protect against electrical shock d to reduce

Technical Specs

Item	Insulated Torque Wrench	Secondary Scale Maximum Torque	2 N-m
Torque Measurement Type	Foot-Pound, Newton-Meter	Ratcheting	Yes
Drive Size	3/8 in	Rotation	Clockwise and Counterclockwise
Torque Range	4 to 20 ft-lb, 5 to 25 N-m	Torque Adjustability	Adjustable
Torque Increments	0.2 N-m	Clockwise Accuracy	+/- 4%
Primary Scale Minimum Torque	4 ft-lb	Counterclockwise Accuracy	+/- 4%
Primary Scale Maximum Torque	20 ft-lb	Corrosion Resistant	Yes
Head Type	Standard	Insulated	Yes
		Nonsparking	No
Secondary Scale Minimum Torque	0.2 N-m	Calibration Certificate Included	Yes

Web Price
\$1,426.99 / each

Qty
1

Add to Cart

☒ Ship

☐ Pickup

⚠ Backordered, expected to arrive by end of Feb, 2022.
Ship to 75201 | [Change](#)

Shipping Weight 2 lbs
[Ship Availability Terms](#)

Add to List

Torque	
Extended Data Testing	No
Torque Setting	Adjustable
Visual/Audible Indicators	Audible Click, Tactile Feedback
Finish	Chrome
Material	Chrome Vanadium steel
Handle Material	Polycarbonate tube
Handle Color	Orange
Dual Scale	Yes
Min. Arc Swing	6 Degrees

Included	
Min. Number of Cycles	5,000
Number of Geared Teeth	60
Overall Length	11 7/32 in
Overall Width	3 5/32 in
Includes	Protective Tube
Standards	ASTM F1505, IEC 60900
Weight	1.68 lb
Head Movement	Standard

