



Onset business statement on COVID-19 impact and response



HOBO Temp/RH 2.5% Data Logger

Part # UX100-011A

Important Info

HOBO data loggers require HOBOWare software and a USB cable. (Note: A USB cable is included with HOBOWare Pro CD or USB software purchase). See compatible items below.

\$125 USD

Overview

The HOBO UX100-011 Temperature/Relative Humidity data logger records temperature and relative humidity (within 2.5% accuracy) in indoor environments with its integrated sensors. This data logger is ideal for monitoring occupant comfort in office buildings, tracking food storage conditions in warehouses, logging temperature trends in server rooms, and measuring humidity levels in museums.

We use cookies to offer you a better browsing experience, analyze site traffic, personalize content and serve targeted advertisements. We take your privacy very seriously. For more information, please read our



[privacy policy](#).

To continue to use our site, please consent to our use of cookies.

Yes

No



Detailed Specifications

HOBO Temp/RH 2.5% Data Logger

Temperature Sensor

Range: -20° to 70°C (-4° to 158°F)

Accuracy: ±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F), see Plot A

Resolution: 0.024°C at 25°C (0.04°F at 77°F); see Plot A

Response time: 4 minutes in air moving 1 m/s (2.2 mph)

Drift: <0.1°C (0.18°F) per year

RH Sensor

Range: 1% to 95% (non-condensing)

Accuracy: ±2.5% from 10% to 90% typical to a maximum of ±3.5% including hysteresis at 25°C (77°F); below 10% and above 90% ±5% typical

Resolution: 0.01%

Response time: 10 seconds to 90% in airflow of 1 m/s (2.2 mph)

Drift: <1% per year typical

Logger

Logger Operating Range

Logging: -20° to 70°C (-4° to 158°F); 0 to 95% RH (non-condensing)

Launch/readout: 0° to 50°C (32° to 122°F) per USB specification

Logging rate: 1 second to 18 hours, 12 minutes, 15 seconds

Logging modes: Normal, Burst or Statistics

Memory modes: Wrap when Full or Stop when Full

Start modes: Immediately, Push Button, Date & Time or Next Interval

Stop modes: When Memory Full, Push Button, or Date & Time

Restart mode: Push Button

Time accuracy: ±1 minute per month at 25°C (77°F), see Plot C

Battery life: 1 year, typical with logging rate of 1 minute and sampling interval of 15 seconds or greater

Battery type: One 3V CR2032 lithium battery

Memory: 128 KB (63,488 measurements, maximum)

Download type: USB 2.0 interface

Full memory download time: 20 seconds

LCD: LCD is visible from: 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range

Size: 3.66 x 8.48 x 2.29 cm (1.44 x 3.34 x 0.9 in.)

Weight: 30 g (1.06 oz)

Environmental rating: IP50

We use cookies to offer you a better browsing experience, analyze site traffic, personalize content and serve targeted advertisements. We take your privacy very seriously. For more information, please read our



[privacy policy](#). To continue to use our site, please consent to our use of cookies.

Yes No



Contact Us

1-508-759-9500 (U.S. and International)
1-800-LOGGERS (U.S. only)
1-800-564-4377 (U.S. only)

Sales/Customer Service
Technical Support
Find a Distributor

Onset Computer Corporation
470 MacArthur Blvd.
Bourne, MA 02532

About Onset

About Onset
Careers
Company Video
Legal
Privacy Policy

News & Events

Press Releases
Trade Shows

Products

All Products
Catalog
Manuals
Software Updates
Firmware Updates
Ordering Information
Quick Order

Support

Knowledge Base
Product Library
User Forum

Stay Connected

Sign up for Email
Read our Blog
Follow us on Social Media

Feedback

Product Suggestions



TrustScore **4.6**
774 reviews

We use cookies to offer you a better browsing experience, analyze site traffic, personalize content and serve targeted advertisements. We take your privacy very seriously. For more information, please read our



[privacy policy](#). To continue to use our site, please consent to our use of cookies.

Yes No