



KODIAK Pressure Gauge with Diaphragm Seal: 0 to 15 psi, KC301/DSM35LP, 2 1/2 in Dial, Mineral Oil

Item **45MU26**
Mfr. Model **KC301L2515/DSM3512LP**

[Product Image Feedback](#) ☐ [Compare](#)

Product Details [Catalog Page N/A](#)

Brand	KODIAK
Accuracy	±1.60%
Accuracy Scale	Full Scale
Adjustable Pointer	No
Ambient Operating Temperature Range	20° to 160°F
Application	Chemical Industries; Highly Corrosive; Hydraulics; Pumps; R/O Systems
Bezel Mounting Type	Crimped
Blowout Safety Back	No
Case Color	Stainless Steel
Case Construction	Corrosion Resistant
Case Depth	1.28 in
Case Diameter	2.8 in
Case Material	Stainless Steel
Cleaned for Oxygen Service	No
Clog Resistant	Yes
Compatible Process Media	Thick or Corrosive Media Compatible with 316 Stainless Steel
Dial Color	White
Diaphragm Seal Process Connection	Threaded
Diaphragm Seal Type	Welded

Web Price **\$133.39** / each

Qty

1

Add to Cart

☒ Ship

☐ Pickup

Expected to arrive **Thu. Aug 01.**
Ship to **78613** | [Change](#)

Shipping Weight **1.75 lbs**
[Ship Availability Terms](#)

[Add to List](#)

Alternate Products



PIC GAUGES Pressure Gauge with Diaphragm Seal: 0 to 15 psi, 301L/3JJJ, 2 1/2 in Dial, Glycerin, Gray
Item **54XN74**

☐ [Compare](#)

Web Price **\$112.02** / each

Qty

1

Add to Cart

Dry Dampening Feature	None
Field Fillable	Yes
Freeze Resistant Movement	No
Gauge Case Liquid	Glycerin
Gauge Case Material	304 Stainless Steel
Hazardous Location Rating	Not Rated
IP/NEMA Rating	NEMA 4X
Includes	Mini Diaphragm Seal
Includes Calibration Certificate	NIST with Data
Includes Mounting Hardware	No
Includes Vent Plug	No
Lens Material	Polycarbonate
Liquid-Filled Case	Yes
Manufacturer Part Number	KC301L2515/DSM3512LP
Manufacturer Warranty Length	1yr
Mounting Type	Stem-Mount
Nominal Dial Size	2-1/2 in
Panel-Mountable	No
Pointer Color	Black
Pointer Material	Aluminum
Pressure Gauge Type	Industrial Pressure Gauge with Diaphragm Seal
Pressure Range	0 to 15 psi
Pressure Range Type	Pressure
Primary Pressure Range	0 to 15
Primary Scale Minor Graduations	0.2
Primary Scale Numeric Increments	3
Primary Scale Units	psi
Process Connection	1/4 in NPT Female
Process Connection Gender	Female
Process Connection Location	Bottom
Process Connection Size	1/4 in
Process Connection Type	NPT
Removable Bezel	No

Scale Type	Dual
Seal Compatible Process Media	Air or Liquid Compatible with 316SS
Seal Connection Size	1/2 in
Seal Diaphragm Material	316 Stainless Steel
Seal External Material	316 Stainless Steel
Seal Fill Liquid	Mineral Oil
Seal Lower Housing Material	316 Stainless Steel
Seal Maximum Working Pressure	2,500 psi
Seal Process Temperature Range	-40° to 400°F
Secondary Pressure Range	0 to 1
Secondary Pressure Scale Color	Blue
Secondary Scale Units	bar
Sensor Material	316 Stainless Steel
Series	KC301; DSM35LP
Socket Material	316 Stainless Steel
Standards	NIST
Vibration Resistance	Liquid-Filled
Wetted Parts Material	316 Stainless Steel/316 Stainless Steel
UNSPSC	23151820
Country of Origin	China (subject to change)

Product Description

Low-pressure gauges have a 316 stainless-steel mini seal with a bellows or diaphragm sensor. These gauges are sold with a mated diaphragm seal that provides a barrier between challenging media like wastewater or wood pulp and the gauge. They are commonly used with natural gas pressure, to test air-flow indication, and detect leaks.

 [Product Details Feedback](#)

 **Compatible Products**



APPROVED VENDOR Thread Sealant Tape: Extra HD, 1/2 in x 21 ft, White

Item **21TF34**

☐ Compare

Web Price 

\$2.23 / each

Qty

1

Add to Cart



ANTI-SEIZE TECH. Thread Seal Tape Assortment: Med Density, 1/2 in x 21 ft, Pink/Yellow

Item **2TE54**

☐ Compare

Web Price 

\$29.00 / each

Qty

1

Add to Cart



ANTI-SEIZE TECH. Thread Sealant Tape: POLY-TEMP® XHD, Extra HD, 1/2 in x 21 ft, White

Item **3PDK9**

☐ Compare

Web Price 

\$4.70 / each

Qty

1

Add to Cart



RECTORSEAL Pipe Thread Sealant: No. 7, 16 fl oz, Brush-Top Can, Black

Item **46F524**

☐ Compare

Web Price 

\$81.95 / each

Qty

1

Add to Cart

