



STURTEVANT RICHMONT

1/4 in Adjustable Drive Torque Screwdriver, Primary Scale Range of 2.00 to 36.00 in-lb

Item #36WD37 Mfr. 810587  
Model #  
UNSPSC27111701 Catalog # 786  
# Page #

This adjustable screwdriver helps to ensure accuracy when securely tightening fasteners. It allows you to

Country of Origin USA. Country of Origin is subject to change.

Web Price *i*  
\$268.00 / each

Qty  
1

Add to Cart

☒ Shipping

☐ Pickup

Availability  
Expected to arrive Thu. Nov 12.  
Ship to 76301 | [Change](#)

Shipping Weight 0.63 lbs  
[Ship Availability Terms](#)

Add to List

Technical Specs

|                                     |                    |
|-------------------------------------|--------------------|
| Screwdriver and Nut Driver Grouping | Screwdrivers       |
| Item                                | Torque Screwdriver |
| Tip Style Group                     | Specialty          |
| Screwdriver Tip Style               | Torque             |
| Tip Size                            | 1/4 in             |
| Overall Length                      | 7 3/4 in           |
| ESD Safe                            | No                 |
| Insulated                           | No                 |
| Nonsparking                         | No                 |

|                                  |               |
|----------------------------------|---------------|
| Handle Design                    | Fluted        |
| Torque Setting                   | Adjustable    |
| Drive Size                       | 1/4 in        |
| Calibration Certificate Included | Yes           |
| Torque Measurement Type          | Inch-Pound    |
| Primary Scale Range              | 2 to 36 in-lb |
| Primary Scale Increments         | 2 in-lb       |
| Rotation                         | CW/CCW        |

Chat with an Agent

|                       |                                                       |
|-----------------------|-------------------------------------------------------|
| Accuracy              | +/-6.0% of Torque Reading @ 20% to 100% Of Full Scale |
| Min. Number of Cycles | 5,000                                                 |

|                  |             |
|------------------|-------------|
| Housing Material | Aluminum    |
| Handle Type      | Fluted      |
| Standards        | ASME B107.3 |

 Chat with an Agent