



Product Categories / Test Instruments / Pressure & Vacuum Measurement / Pressure & Vacuum Gauges / Industrial & Process Pressure Gauges / Dial Industrial Pressure Gauges / Industrial Pressure Gauge: 0 to 300 psi, 4 in D...

PIC GAUGES

Industrial Pressure Gauge: 0 to 300 psi, 4 in Dial, Liquid-Filled, 1/2 in NPT Male, 201L

Item #20TV74

Mfr. Model #201L-402H

UNSPSC #23151820

Catalog Page #579

Country of Origin China. Country of Origin is subject to change.

Crimped bezel gauge comes standard with glycerine fill and is suitable for applications where

Technical Specs

|                           |                           |                             |               |
|---------------------------|---------------------------|-----------------------------|---------------|
| Item                      | Industrial Pressure Gauge | Field Fillable              | No            |
| Nominal Dial Size         | 4 in                      | Process Connection Location | Bottom        |
| Accuracy                  | +/-1.0%                   | Case Color                  | Metallic      |
| Gauge Case Material       | Stainless Steel           | IP/NEMA Rating              | Not Rated     |
| Process Connection Type   | NPT                       | Primary Pressure Range      | 0 to 300      |
| Process Connection Gender | Male                      | Dry Dampening Feature       | None          |
| Lens Material             | Polycarbonate             | Vibration Resistance        | Liquid-Filled |



Web Price

\$52.95 / each

Qty1

Add to Cart

☒ Ship

☐ Pickup


Expected to arrive **Mon. Dec 27.**

Ship to 75201 | [Change](#)


Shipping Weight 1.7 lbs

[Ship Availability Terms](#)

Add to List



|                                     |                             |                                  |            |
|-------------------------------------|-----------------------------|----------------------------------|------------|
| Process Connection Size             | 1/2 in                      | Dial Color                       | White      |
| Pressure Gauge Type                 | Industrial Pressure Gauge   | Cleaned for Oxygen Service       | No         |
| Liquid-Filled Case                  | Yes                         | Dial Face Material               | Aluminum   |
| Gauge Case Liquid                   | Glycerin                    | Freeze Resistant Movement        | No         |
| Panel-Mountable                     | No                          | Hazardous Location Rating        | Not Rated  |
| Socket Material                     | Copper Alloy                | Includes                         | Vent Plug  |
| Sensor Material                     | Copper Alloy                | Includes Calibration Certificate | No         |
| Accuracy Grade                      | ASME B40.100 Grade 1A       | Includes Mounting Hardware       | No         |
| Series                              | 201L                        | Includes Vent Plug               | Yes        |
| Application                         | General Purpose             | Manufacturer Warranty Length     | 1 yr       |
| Primary Scale Units                 | psi                         | Mounting Type                    | Stem-Mount |
| Accuracy Scale                      | Full Scale                  | Non-Sparking                     | No         |
| Ambient Operating Temperature Range | 30 Degrees to 160 Degrees F | Pointer Color                    | Black      |
| Bezel Material                      | Stainless Steel             | Pointer Material                 | Aluminum   |
| Bezel Mounting Type                 | Fixed                       | Pressure Range Type              | Pressure   |
| Blowout Safety Back                 | No                          | Primary Scale Minor Graduations  | 5          |
| Case Depth                          | 1.75 in                     | Removable                        | No         |


 Chat with an Agent

|                          |         |                       |      |
|--------------------------|---------|-----------------------|------|
| Case Diameter            | 4.29 in | Removable Bezel       | Yes  |
| Scale Type               | Dual    | Secondary Scale Units | bar  |
| Secondary Pressure Range | 0 to 21 | Standards             | ASME |

Compliance and Restrictions

 WARNING Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

 Chat with an Agent