



196B5 Universal Back Plunger Dial Indicator 50717

196, 196M Universal Back-Plunger Dial Test Indicators

Back Plunger Dial Indicator, .200" Range, 0-50-0 Dial Face, .001" Graduations, 3 Contact Points and Adaptor

The Starrett 196 Universal Back Plunger Dial Indicator features graduations to .001" and 0.02mm that handle by far the majority of jobs. Shank diameter is 1/4" (6.3mm). Antimagnetic models are also available - (inch reading) 196A6Z and 196B6. For full use, the operator first chooses the proper contact from the three hardened contact points that come with each model. Then the contact should be brought against the work with enough pressure to give the hand one full turn. Set the hand

at zero by rotating the dial with the knurled bezel. This provides one full rotation of the hand both to the right and left of zero, showing a rise or drop in the work and the amount of that variation. 0-50-0 with 3 Contact Points and Adapter only This provides one full rotation of the hand both to the right and left of zero, showing a rise or drop in the work and the amount of that variation.

- » FEATURES
- » SPECIFICATIONS
- » PARTS
- » DOWNLOADS
- » 3D CAD FILES / EXPLODED PARTS DIAGRAM
- » PRODUCT TESTIMONIALS
- » CALIFORNIA PROP 65

Catalog Number: **196B5**
EDP Number: **50717**

List Price: \$203.00 USD Ea

1

 ADD TO CART

Other similar products

▼





 CONTACT STARRETT

FEATURES

⬆

SPECIFICATIONS

⬆

✓ Made in America: Yes

✓ Range (in): .200"

✓ Graduations (in): .001"

✓ Dial Reading: 0-50-0

✓ Attachments: Indicator with 3 Contact Points and Adaptor Only

✓ Dial Color: White

⬆