



## Shopping Cart

Your cart is empty.

Select ...



## Categories

[\\*Dead Stock\\* - Clearance](#)

[Accessories/Replacement](#)

[Adapters/Fittings/Hoses/Kits](#)

[Air Filtration](#)

[Air Velocity / Wind Direction](#)

[Alarm System](#)

[Analyzer](#)

[Ballistics](#)

[Cable Tester](#)

[Calibration Furnaces](#)

[Calibration Manifolds and Fittings](#)

[Calibration Services](#)

[Calibration Stations](#)

[Calibration Sytems](#)

[Calibrators](#)

[Chart Recorders](#)

[Conductivity](#)

[Controller](#)

[Current/Voltage](#)

[Deadweight Testers](#)

[Decade Box](#)

[Differential Pressure](#)

[Digital Multi-meters](#)

[Digital Pressure Gauge](#)

[Dimensional Measurement Tools](#)

[Drains](#)

[Equipment Cases](#)

[Explosion Proof](#)

[Filters](#)

[Fixed Systems](#)

[Flow Meter](#)

[Flow Switch](#)

[Gas Detector](#)

[Home](#) > [Pressure](#) > McDaniel Stainless Steel, 2.5" Dial Gauges Model-J & Model-K

## McDaniel Stainless Steel, 2.5" Dial Gauges Model-J & Model-K

[<< Previous in Pressure](#)



Price: **\$83.65**

Item Number: **J-K**

Manufacturer: **MCDANIEL CONTROLS**

### Choose Your Model

Model: "J" (SS case, brass internals, up to 1000 psi)

Pressure Range: 0-1000 psi

Mounting Style: Standard Bottom

### Options

\* denotes required field

Connection Size \*

- ☒ 1/4" NPT (Standard)
- ☐ 1/8" NPT (Special Order) (+ \$4.40)
- ☐ 1/4" Medium Pressure Male connection (K Model)
- ☐ 1/4" Medium Pressure Female connection (J Model)
- ☐ 1/4" High Pressure Male connection (K Model)

Custom Scale (Optional) \*

psig (default)

Special Configurations and Options

- ☐ Calibration Chart (+ \$114.00)
- ☐ Reed Switch/Single (For Model K) (+ \$180.30)
- ☐ Cleaned for Oxygen Service Model K (Factory Clean) (+ \$19.80)
- ☐ Cleaned for Oxygen Service Model J (Factory Clean) (+ \$10.00)
- ☐ Reed Switch/Single (For Model J) (+ \$199.20)

Liquid Filled Option

Select ...

Quantity: 1

[Add To Cart](#)

[Add to a new shopping list](#)

[Email this page to a friend](#)

## McDaniel Controls Stainless Steel 2.5" Dial Gauge

McDaniel Controls Models "J" and "K" gauges are the most accurate, corrosion resistant, and rugged gauges you can buy in a 2 1/2" dial size.

Ideal for use as a positioned gauge on valves where vibration and corrosion are a problem. (Check the dimensionals. Some enclosures will not accept the face to stem tip depth!) These gauges will withstand harsh chemical environments and the glycerin filling shuts out corrosive atmospheres, while offering maximum protection from vibration and pulsation. It's accuracy of 1% of full scale value is unique in this size gauge.

### Standard and Optional Features:

Dial size: 2.5 inch (63mm)

|                                                    |
|----------------------------------------------------|
| <a href="#">Gas Meter</a>                          |
| <a href="#">Gas Monitor</a>                        |
| <a href="#">Gas Sensors</a>                        |
| <a href="#">Gas Test</a>                           |
| <a href="#">Gaskets</a>                            |
| <a href="#">Gauge</a>                              |
| <a href="#">Ground Resistance Testers</a>          |
| <a href="#">Hart Communicators</a>                 |
| <a href="#">Heat Stress Index</a>                  |
| <a href="#">Helium</a>                             |
| <a href="#">Humidity</a>                           |
| <a href="#">HVAC</a>                               |
| <a href="#">Indoor Air Quality</a>                 |
| <a href="#">Industrial Acoustic Imager</a>         |
| <a href="#">Infrared</a>                           |
| <a href="#">Infrared Distance Learning Courses</a> |
| <a href="#">Insulation Tester</a>                  |
| <a href="#">Intrinsically safe</a>                 |
| <a href="#">Leak Detection</a>                     |
| <a href="#">Leasing Options</a>                    |
| <a href="#">Megohmmeter - Insulation Testers</a>   |
| <a href="#">Membrane Dryers</a>                    |
| <a href="#">Micro-Ohmmeter</a>                     |
| <a href="#">Moisture</a>                           |
| <a href="#">Panelmeters</a>                        |
| <a href="#">pH Sensors</a>                         |
| <a href="#">Power Analyzer/Energy Datalogger</a>   |
| <a href="#">Power Supply</a>                       |
| <a href="#">Pressure</a>                           |
| <a href="#">Absolute Pressure</a>                  |
| <a href="#">Bench Standards</a>                    |
| <a href="#">Comparators</a>                        |
| <a href="#">Controllers</a>                        |
| <a href="#">Dataloggers</a>                        |
| <a href="#">Deadweight Testers</a>                 |
| <a href="#">Diaphragm Seals</a>                    |
| <a href="#">Field Calibrators</a>                  |
| <a href="#">Laboratory</a>                         |
| <a href="#">Pressure Gauges</a>                    |
| <a href="#">Pressure Switches</a>                  |
| <a href="#">Pumps</a>                              |
| <a href="#">Recorders</a>                          |
| <a href="#">Transmitters</a>                       |
| <a href="#">Vacuum Pressure</a>                    |
| <a href="#">Pressure and Temperature Recorders</a> |
| <a href="#">Pressure Modules</a>                   |
| <a href="#">Probes</a>                             |

|                       |                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------|
| Fillable:             | Yes                                                                                                   |
| Connection:           | 1/4" NPT Standard (1/8" NPT available on special request)                                             |
| Case:                 | 304 Stainless Steel                                                                                   |
| Internals:            | 316 Stainless Steel (Model K) / Brass (Model J)                                                       |
| Wetted parts:         | 316 Stainless Steel Heavy Duty Connection, Socket and Bourdon Tube (Model K) / Brass/Bronze (Model J) |
| Accuracy:             | 1% ASME B40.1 Grade 1A                                                                                |
| Ranges:               | Up to 20,000 psi (Model K) / Up to 6,000 psi (Model J)                                                |
| Mount:                | Standard Bottom, Lower-Back, U-Clamp, Panel Mount, Rear Flange, Center-Back                           |
| Scale:                | psi/Bar (dual scale), psi/kPa (dual scale), psi/kg/cm2 (dual scale)                                   |
| Options:              | Cleaned for oxygen service                                                                            |
| Choice(s) of filling: | Glycerin, Silicone                                                                                    |

Features:

Laminated Safety Glass Lens  
Repairable  
Weather Tight Case  
Restrictor screw for pulsation dampening  
Solid Front Blow-out Case Available  
Fillable Case  
Accuracy: \*1% ASME B40.1 Grade 1A

(\* 10,000 PSI and below)

Safe and Reliable:

McDaniel designs and manufactures its gauges to minimize failure and to protect personnel and property. The use of laminated safety glass, rather than plexiglass or single strength glass, prevents dangerous pressure build-up in the case; the 2" glass breaks at 60 psi, the 2 ½" at 40 psi, the 4" at 15 psi and the 6" at 8 psi. The brittle glass cracks uniformly and the laminate remains intact. Additionally, the laminated safety glass won't craze or discolor.

Every All Stainless Steel McDaniel gauge is designed to withstand:

- 300% full scale pressure without rupture of the bourdon tube.
- 130% full scale pressure without loss of accuracy.
- 15,000 cycles of pressure pulsation from 10% to 90% full scale at a rate of 60 times a minute. The gauge is allowed to rest for 5 minutes and then can have no greater error than 1% above it's original accuracy as stated above; at any place on the dial.

Pulse/Vibration Protection:

McDaniel offers liquid-filled gauges for applications involving vibration or pulsation. Glycerin is an excellent damper of bourdon tube movement. Emersion of the entire measuring assembly in a protective liquid envelope provides lubrication and shuts out corrosive or dirty atmospheres -- thereby minimizing wear of moving parts and prolonging gauge life significantly.

Choices of Mounting Style

- Standard bottom
- Lower-Back
- U-Clamp
- Panel Mount
- Rear Flange
- Center Back

Choice of Scale

McDaniel offers from inventory many dual scale ranges. These include psi/kPa with the psi scale primary and kPa secondary; psi/Bar with the psi scale primary and Bar secondary; psi/kg/cm² with psi primary and kg/cm² secondary; kg/cm²/psi with kilograms per cm² primary and psi secondary

Choice of Filling:

When you order a McDaniel fillable gauge you may choose to fill it yourself or you may order it factory-filled with the liquid of your choice. Thus, you can maximize inventory utility and minimize inventory cost.

Glycerin filling has a lower operating temperature limit of 32°F (0°C) undiluted. The mixture of distilled water in proportions up to 35% will lower the limit commensurately, to -40°F (-40°C).

Silicone can extend the lower temperature limit to -60°F (-50°C).

The maximum temperature limit is not determined by the fluid but by the gauge's synthetic case seal. At elevated temperatures the seal may bake and lose its elasticity.

Warning: Glycerin filled gauges should not be used in applications involving strong oxidizing agents such as chlorine, nitric acid or hydrogen peroxide. (Refer to ASME B40.1)

Repair Feature:

If any McDaniel gauge requires repair, downtime can be minimal because all gauges are field-repairable - quickly and easily - with only a screwdriver needed for disassembly.

If circumstances permit and factory repair is preferred, we will make the repair at a nominal service charge. See "WARRANTY & REPAIR" for further details

**Warranty**  
McDaniel warrants our pressure gauges to be free of defects in material and workmanship. Replacement of any defective gauge will be made at no cost to the purchaser. Gauge failures determined to be caused by abuse, over-range and incompatibility with environment or process media will not be considered under this warranty.

**Repair / Refurbish**  
We will repair and/or refurbish any regular stock McDaniel gauge for a charge to be determined after the gauge is examined by our Quality Control Department. Damaged sockets or bourdon tubes cannot be repaired.

Durable

The best-known construction materials available are used in the manufacture of McDaniel gauges.

Spiral Bourdon Tube

Bourdon tube work hardening can cause premature rupture in a pulsation type service, especially if that service is above 800 psi, where heavy wall thickness of the Bourdon tube is encountered.

McDaniel therefore, incorporates an annealed spiral bourdon tube as the sensing element of all gauge ranges above 800 psi to minimize bourdon tube failure possibilities.

\*\*To Order Seals Please Call (610) 446-6600. See Related Products to View\*\*

Gauge Model Selection Guide

|              |       |     |      |           |          |        |
|--------------|-------|-----|------|-----------|----------|--------|
| DIAL<br>SIZE | MODEL | NPT | CASE | INTERNALS | ACCURACY | RANGES |
|--------------|-------|-----|------|-----------|----------|--------|

- [Pulsation Dampener](#)
- [Pumps](#)
- [Recorders/Dataloggers](#)
- [Regulators](#)
- [Separator](#)
- [Software](#)
- [Specialty Products](#)
- [Spray Shield](#)
- [Switches](#)
- [Tachs And Strokes](#)
- [Temperature](#)
- [Thermal Camera](#)
- [Thermocouples](#)
- [Thermometers](#)
- [Thickness Gage](#)
- [Time Domain Reflectometer](#)
- [Torque Wrenches](#)
- [Transducer](#)
- [Transformer](#)
- [Transformer Ratiometer](#)
- [Transmitters](#)
- [Vacuum](#)
- [Valve Adapters](#)
- [Valves](#)
- [Velocity Vibration Sensor](#)
- [Vibration Pen](#)
- [Vibration Switch](#)
- [Weather/Environmental Meter](#)

|                  |                  |                 |                      |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|------------------|------------------|-----------------|----------------------|-------------------------|-------------------------|--------------------------------------|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| 1½"<br>(40 mm)   | <b><u>S</u></b>  | 1/8"            | 304 STAINLESS STEEL  | 316 STAINLESS STEEL (2) | 1.5% Grade A            | Up to 10,000 psi                     | • Full blow-out<br>• Lexan Lens<br>• Compensating                                     |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | * 1/4"          | Fillable             |                         |                         |                                      | <b>MOUNTING ST</b><br>Bottom, Center-                                                 |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>R7</u></b> | 1/8"            | 304 STAINLESS STEEL  | BRASS (3)               | 3-2-3% Grade B          | Up to 5,000 psi                      | • Utility Gauge<br><br>• Polycarbonate<br><br>• Economical M<br><br>• Restrictor scre |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | * 1/4"          | Non-Fillable         |                         |                         |                                      | <b>MOUNTING ST</b><br>Bottom, Center-                                                 |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>R8</u></b> | 1/8"            | BLACK ENAMELED STEEL |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | * 1/4"          | Non-Fillable         |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
| 2"<br>(50 mm)    | <b><u>Q3</u></b> | 1/8"            | 304 STAINLESS STEEL  | 316 STAINLESS STEEL (2) | 1% Grade 1A             | Up to 15,000 psi                     | • Laminated Sa<br>• Weather Tight                                                     |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Fillable             |                         |                         |                                      | <b>MOUNTING ST</b><br>Bottom, Center-                                                 |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>T6</u></b> | 1/8"            | 304 STAINLESS STEEL  | BRASS (3)               | 3-2-3% Grade B          | Up to 5,000 psi                      | • Utility Gauge<br><br>• Polycarbonate<br><br>• Economical M<br><br>• Restrictor scre |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Filled**             |                         |                         |                                      | <b>MOUNTING ST</b><br>Bottom, Center-                                                 |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>T7</u></b> | 1/8"            | 304 STAINLESS STEEL  |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Non-Fillable         |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>T8</u></b> | 1/8"            | BLACK ENAMELED STEEL |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Non-Fillable         |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | 2½"<br>(63 mm)   | <b><u>K</u></b> | * 1/8"               | 304 STAINLESS STEEL     | 316 STAINLESS STEEL (2) | 1% Grade 1A                          | Up to 20,000 psi                                                                      | • Laminated Sa<br>• Repairable<br>• Weather Tight<br>• Restrictor scre<br>• Solid Front Bl |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  |                 | 1/4"                 | Fillable                |                         |                                      |                                                                                       | <b>MOUNTING ST</b><br>Bottom, Lower-I<br>Flange, Center-                                   |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | <b><u>J</u></b> | * 1/8"               | 304 STAINLESS STEEL     | BRASS (3)               |                                      | 2-1-2% Grade A                                                                        | Up to 6,000 psi                                                                            | • Laminated Sa<br>• One-piece cas                                                     |                                                                                                                                                                   |                                                       |
|                  |                  |                 | 1/4"                 | Fillable                |                         |                                      |                                                                                       |                                                                                            | <b>MOUNTING ST</b><br>Bottom, Center-                                                 |                                                                                                                                                                   |                                                       |
| <b><u>U</u></b>  |                  | * 1/8"          | CAST BRASS           | 316 STAINLESS STEEL (2) |                         |                                      |                                                                                       | Up to 10,000 psi                                                                           | • Polycarbonate<br>• Rolled Threac                                                    |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Fillable             |                         |                         |                                      |                                                                                       |                                                                                            | <b>MOUNTING ST</b><br>Bottom, Lower-I<br>Flange                                       |                                                                                                                                                                   |                                                       |
| <b><u>K9</u></b> |                  | * 1/8"          | 304 STAINLESS STEEL  | BRASS (3)               | 3-2-3% Grade B          | Up to 15,000 psi                     |                                                                                       | • Utility Gauge<br><br>• Polycarbonate<br><br>• Economical M<br><br>• Restrictor scre      |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Fillable             |                         |                         |                                      |                                                                                       | <b>MOUNTING ST</b><br>Bottom, Center-                                                      |                                                                                       |                                                                                                                                                                   |                                                       |
| <b><u>J6</u></b> |                  | * 1/8"          | 304 STAINLESS STEEL  | 316 STAINLESS STEEL (2) |                         | 3-2-3% Grade B                       | Inches of Water* & Up to 15,000 psi                                                   | • Utility Gauge<br><br>• Polycarbonate<br><br>• Economical M<br><br>• Restrictor scre      |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Filled**             |                         |                         |                                      |                                                                                       | <b>MOUNTING ST</b><br>Bottom, Center-                                                      |                                                                                       |                                                                                                                                                                   |                                                       |
| <b><u>J7</u></b> |                  | * 1/8"          | 304 STAINLESS STEEL  |                         |                         |                                      | BRASS (3)                                                                             | 2-1-2% Grade A                                                                             | Up to 10,000 psi                                                                      | • Polycarbonate<br>• Rolled Threac                                                                                                                                |                                                       |
|                  |                  | 1/4"            | Non-Fillable         |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       | <b>MOUNTING ST</b><br>Bottom, Lower-I<br>Flange                                                                                                                   |                                                       |
| <b><u>J8</u></b> |                  | * 1/8"          | BLACK ENAMELED STEEL | BRASS (3)               | 3-2-3% Grade B          |                                      | Inches of Water* & Up to 15,000 psi                                                   |                                                                                            | • Utility Gauge<br><br>• Polycarbonate<br><br>• Economical M<br><br>• Restrictor scre |                                                                                                                                                                   |                                                       |
|                  |                  | 1/4"            | Non-Fillable         |                         |                         |                                      |                                                                                       |                                                                                            | <b>MOUNTING ST</b><br>Bottom, Center-                                                 |                                                                                                                                                                   |                                                       |
| 4"<br>(100 mm)   |                  | <b><u>A</u></b> | 1/4"                 | 304 STAINLESS STEEL     |                         | 316 STAINLESS STEEL (2)              | .5%† Grade 2A                                                                         |                                                                                            | Inches of Water And Up to 35,000 psi                                                  | • Laminated Sa<br>• Repairable<br>• Adjustable Po<br>• No pointer stc<br>• Pulsation Dam<br>• Full blow-out<br>• Vacuum Stop<br>• Overrange St<br>• Weather Tight |                                                       |
|                  |                  | <b><u>C</u></b> | 1/2"                 | Non-Fillable            |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | <b><u>E</u></b> | 1/4"                 | 304 STAINLESS STEEL     |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  |                  | <b><u>G</u></b> | 1/2"                 | Fillable                |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>L</u></b>  | 1/4"            | POLYAMID "B"         | BRASS (3)               | .5%† Grade 2A           | Inches of Water And Up to 35,000 psi |                                                                                       | <b>MOUNTING ST</b><br>Bottom, Lower-I<br>Front Flange, R                                   |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>M</u></b>  | 1/2"            | Non-Fillable         |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>N</u></b>  | 1/4"            | POLYAMID "B"         |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>P</u></b>  | 1/2"            | Fillable             |                         |                         |                                      |                                                                                       |                                                                                            |                                                                                       |                                                                                                                                                                   |                                                       |
|                  | <b><u>E9</u></b> | 1/4"            | 304 STAINLESS STEEL  | 316 STAINLESS STEEL (2) |                         |                                      |                                                                                       | 2-1-2% Grade A                                                                             |                                                                                       | Up to 10,000 psi                                                                                                                                                  | • Polycarbonate<br>• Rolled Threac<br>• Threaded Inle |

|                           |               |      |                                            |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|---------------------------|---------------|------|--------------------------------------------|-------------------------|------------------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                           | <b>G9</b>     | 1/2" | Fillable                                   |                         |                  |                                          | <b>MOUNTING ST</b><br>Bottom, Center,                                                                                                                                                                                                                                                                                                    |
|                           | <b>MCXA</b>   | 1/4" | 304 STAINLESS STEEL                        | 316 STAINLESS STEEL (2) | 1.5%<br>Grade A  | 6"-160" WC                               | <ul style="list-style-type: none"> <li>Laminated Se</li> <li>Repairable</li> <li>Weather Tigh</li> <li>Capsule Sens</li> <li>20 times Over</li> <li>Precision Gea</li> <li>Vacuum and (</li> </ul>                                                                                                                                       |
|                           | <b>MCXC</b>   | 1/2" | Non-Fillable                               |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|                           | <b>MC3A</b>   | 1/4" | ALLOY STEEL                                | BRASS (3)               | 1.5%<br>Grade A  | 4"-160" WC                               | <b>MOUNTING ST</b><br>Bottom, Lower-I                                                                                                                                                                                                                                                                                                    |
|                           | <b>MC3C</b>   | 1/2" | Non-Fillable                               |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
| <b>4 1/2"</b><br>(130 mm) | <b>MPB/SA</b> | 1/4" | FIBERGLASS REINFORCED THERMOPLASTIC (PBTP) | 316 STAINLESS STEEL (2) |                  | Up to 20,000 psi                         | <ul style="list-style-type: none"> <li>Laminated Se</li> <li>Adjustable Pc</li> <li>Compensatin</li> <li>"O" ring seal</li> <li>sealed, weathe</li> </ul> <b>MOUNTING ST</b><br>Bottom Connec                                                                                                                                            |
|                           | <b>MPB/SC</b> | 1/2" | Fillable                                   |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
| <b>6"</b><br>(160 mm)     | <b>B</b>      | 1/4" | 304 STAINLESS STEEL                        | 316 STAINLESS STEEL (2) | .5%†<br>Grade 2A | Inches of Water and Up to 60,000 psi (4) | <ul style="list-style-type: none"> <li>Laminated Se</li> <li>Repairable</li> <li>Adjustable Pc</li> <li>No pointer st</li> <li>Pulsation Dar</li> <li>Full blow-out</li> <li>Vacuum Stop</li> <li>Overrange St</li> <li>Weather Tigh</li> </ul> <b>MOUNTING ST</b><br>Bottom, Lower-Front Flange, R<br>(MODELS: F, H<br>Solid Front/Blov |
|                           | <b>D</b>      | 1/2" | Non-Fillable                               |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|                           | <b>F</b>      | 1/4" | 304 STAINLESS STEEL                        |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|                           | <b>H</b>      | 1/2" | Fillable                                   |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|                           | <b>Y</b>      | 1/4" | POLYAMID "B"                               | BRASS (3)               |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|                           | <b>Z</b>      | 1/2" | Non-Fillable                               |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|                           | <b>MCXB</b>   | 1/4" | 304 STAINLESS STEEL                        | 316 STAINLESS STEEL (2) | 1.5%<br>Grade A  | 2.5"-160" WC                             | <ul style="list-style-type: none"> <li>Laminated Se</li> <li>Repairable</li> <li>Weather Tigh</li> <li>Capsule Sens</li> <li>20 times Ove</li> <li>Precision Gea</li> <li>Vacuum and (</li> </ul>                                                                                                                                        |
|                           | <b>MCXD</b>   | 1/2" | Non-Fillable                               |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |
|                           | <b>MC3B</b>   | 1/4" | ALLOY STEEL                                | BRASS (3)               | 1.5%<br>Grade A  | 1.6"-160" WC                             | <b>MOUNTING ST</b><br>Bottom, Lower-                                                                                                                                                                                                                                                                                                     |
|                           | <b>MC3D</b>   | 1/2" | Non-Fillable                               |                         |                  |                                          |                                                                                                                                                                                                                                                                                                                                          |

\* SPECIAL    \*\* FILLED  
NON-STOCK    GLYCERIN

ACCURACY  
ASME B40.1

RANGE  
Includes: Vacuum, Compound, and Receiver 3-15  
(1) Model "S" 1  
(2) 316 SS Tub  
(3) Brass Sock  
Tube and Tip.  
(4) Models Y ar

Related Products

|                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>R8</div>  <p><b>McDaniel 1.5" Economy Positioner Gauges</b><br/>Price: <b>From \$14.35 to \$18.90</b></p> <p><a href="#">Details</a></p> <p>1.5" Economy Positioner Gauges. Ideal for use as positioner gauges, the models R7 and R8 are also ideal OEM gauges.</p> | <div></div>  <p><b>REOTEMP DSHS Series Hygienic Diaphragm Seals</b><br/>Price: <b>Call for pricing</b></p> <p><a href="#">Details</a></p> <p>REOTEMP's Series DSHS Diaphragm Seals incorporate a number of various connections used in the sanitary and hygienic markets. Ideal for applications in the Pharmaceutical, Dairy, and Food &amp; Beverage market.</p> | <div>Q3</div>  <p><b>McDaniel All Stainless Steel Gauges</b><br/>Price: <b>From \$14.35 to \$42.50</b></p> <p>The model "Q3" gauge is resistant and rugged. Features all stainless steel lens, blowout relief gasket, and OEM connections.</p> |
| <div></div>  <p><b>McDaniel Controls Stainless Steel Case 2" Utility Gauges</b><br/>Price: <b>From \$14.35 to \$42.50</b></p> <p><a href="#">Details</a></p>                                                                                                             | <div>E</div>  <p><b>McDaniel 4" All Stainless Steel Gauges</b><br/>Price: <b>From \$156.15 to \$392.70</b></p> <p><a href="#">Details</a></p>                                                                                                                                                                                                                      | <div>B</div>  <p><b>McDaniel 6" All Stainless Steel Gauges</b><br/>Price: <b>From \$156.15 to \$392.70</b></p> <p><a href="#">Details</a></p>                                                                                                  |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>Details</div> <p>The models "T6", "T7", and "T8" gauges are the best value you can buy in a 2" dial. T6 features stainless steel case and brass internals for corrosion resistance, laminated safety glass lens, blowout relief grommet and a fillable case.</p>                                                                                                                                                                                                                                                                                                                                              | <p>McDaniel designs and manufactures its gauges to minimize failure and to protect personnel and property. The use of laminated safety glass, rather than plexiglass or single strength glass, prevents dangerous pressure build-up in the case.</p> <p>McDaniel design: minimize failure and t use of laminated sa single strength glass</p> |
| <div>A circular pressure gauge with a black dial and white face, labeled 'MPB/SC' at the top. The dial has markings from 0 to 30. The gauge has a green base and a black mounting bracket.</div> <div>McDaniel Controls 4.5" Process Gauges</div> <div>Price: <b>From \$208.20 to \$363.30</b></div> <div>After Discount: <b>From \$166.56 to \$290.64</b></div> <div>Details</div> <p>McDaniel designed the model MPB/S to meet and exceed the rigorous and harsh requirements of the process, petrochemical, and power industries. With safety also a major consideration, McDaniel developed the MPB/S with</p> |                                                                                                                                                                                                                                                                                                                                               |
| <div><a href="#">Home</a>   <a href="#">About Us</a>   <a href="#">Contact Us</a>   <a href="#">My Account</a>   <a href="#">Shipping Policy</a>   <a href="#">Return Policy</a>   <a href="#">Privacy Policy</a>   <a href="#">Sitemap</a>   <a href="#">Cart Help</a>   <a href="#">Financing</a></div> <div>© 2023Instrumentation.com - A Shelby Jones Co.</div>                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                               |