

The TS-Series has been discontinued by Ohaus. Our replacement is the **A&D HF-Series**. This web page is here for reference only when a customer is reviewing the specifications of their TS-Series to replace with a new **A&D HF-Series**.

The Precision Standard Series Toploading Balances These precision balances feature advanced construction and rugged design to give you outstanding performance and durability. Die-cast metal cases, large stainless steel platforms, and shock-absorbing pan supports are just a few of the additional quality features you'll find. The TS Series have simple two-button operation, calibration lock-out switch, adjustable stability and averaging levels, and weigh below capacity. All models are UL-listed, comply with FCC regulations, and include a power adapter with 6-ft cord. In addition, the TS-Series is back with a 5 year manufacturer's warranty.



<http://www.balances.com>

SPECIFICATIONS

buy it <i>PRECISION STANDARD, TS SERIES</i> buy it						
Model Number	TS200†	TS600	TS400D†‡	TS2K	TS4K	TS4KD‡
PRECISION WEIGHING BALANCES DISCOUNT PRICE	\$845.00	\$762.00	\$ 975.00	\$977.50	\$867.00	\$ 999.99
CAPACITY (grams)	200	600	400/80	2000	4000	4000/800
READABILITY (g)	0.001	0.01	0.01/0.001	0.01	0.1	0.1/0.01
LINEARITY (g)	± 0.002	± 0.01	± 0.01/0.002	± 0.02	± 0.1	± 0.1/0.02
WEIGHING MODES (g)	g, lb, oz, lb:oz, ct, dwt, tals (3), oz t, gn, mommes					
REPEATABILITY (standard deviation) (g)	0.001	0.007	0.007/0.001	0.01	0.07	0.07/0.01
TARE RANGE	Full capacity by subtraction					
STABILIZATION TIME	2.5 Seconds					
PLATFORM SIZE (in/cm)	4.8" / 12.2 cm diameter			6 " x 6.5" / 15.2 cm x 16.5 cm		
OPERATING TEMPERATURE RANGE ° F	50 ° - 104 ° F					
AC POWER	100, 120, 220, 240 VAC, 50/60 Hz					
CALIBRATION	External digital calibration					
DISPLAY	LCD (0.6 inches/ 1.5 cm High)					
DIMENSIONS (W x H x D) (in/mm)	8.5" x 3.75" x 14.5" 216mm x 95mm x 368mm without draft shield					
NET WEIGHT	10.4 lbs. / 4.7 kg					

(approx.) (lb/kg)	
SHIPPING WEIGHT (approx.) (lb/kg)	13.6 lbs. / 6.2 kg
<u>OPTIONAL FEATURES</u>	Security device, Draft Shield for TS600, RS-232 Interface, Weigh below hook, Data Printer, In-service cover, Calibration Mass
	

- † Draft Shield Included on TS200 and TS400D
‡ TS400D and TS4KD have two ranges called Dual Range

Note: Prices are for 110V power adapters. For other voltages add \$ 20.00 ea.
Specifications subject to change without notice

Back to the Ohaus Precision Family Table of Contents.

A&D HF Series offer a huge selection of models for any of your weighing needs.



See the complete line of A&D High Capacity Industrial Scales. Weighing capacities from 12 kg to 101 kg and accuracy to 0.1 g.



Search our site:

SEARCH

[Hot Buys](#) | [Analytical Balances](#) | [Baby Scales](#) | [Calibration Weights](#) | [Counting Scales](#) | [Crane Scales](#) | [Industrial Platform & Bench Scales](#) | [Mechanical Balances](#) | [Medical Scales](#) | [Moisture Balances](#) | [Pocket Scales](#) | [Portable Balances](#) | [Precision Toploader Balances](#) | [Price Computing Scales](#) | [Vet Scales](#) | [Wheelchair Scales](#) | [USED & Demo Balances](#) | [Contact Us](#) | [Return Policy](#) | [Home](#)

Have Questions? Call 978-521-7095 or e-mail us your questions and we will assist you in your selection.

Copyright © 2017 [Precision Weighing Balances](#), All Rights Reserved.
<https://www.balances.com>, balances.net, scaleman.com, scalenet.com, weigh.net, weigh.org, analytical-balances.com, lab-balances.com, moisture-balances.com, precision-balances.com, [scale-galore.com](#), [scales-galore.com](#) & [calibrationweight.com](#) are all registered domains of Precision Weighing Balances.

◀ Previous