

SHAHE

SF Digital Push Pull Gauge



Specification

Model	SF-2	SF-3	SF-5	SF-10	SF-20	SF-30	SF-50	SF-100	SF-200	SF-300	SF-500
The max. Load value	2N	3N	5N	10N	20N	30N	50N	100N	200N	300N	500N
	0.2kg	0.3kg	0.5kg	1kg	2kg	3kg	5kg	10kg	20kg	30kg	50kg
	0.45Lb	0.65Lb	1.1Lb	2.2Lb	4.5Lb	6.5Lb	11Lb	22Lb	45Lb	65Lb	110Lb
Load Value	0.001N			0.01N				0.1N			
	0.001KG			0.001KG				0.01KG			
	0.001Lb			0.001Lb				0.01Lb			
The sensor	Sensor inside										
Precision	± 0.5%										
Power	3.7V lithium battery										
Charging time	4~6 hours										
Continuous usage time of battery	About 15 hours										
Battery life	≥ 300 times										
Charger	Input: AC100- 240V 50-60Hz Output: DC 5V 1000mA										
Working temperature	5 °C ~35 °C										
Transportation temperature	-10 °C~60°C										
Relative humidity	15%~80%RH										
Work environment	No focus ,Non-corrosive in surroundings										

<https://www.shahemeasuring.com/force-measuring-instruments/sf-digital-push-pull-gauge>