



CALL TOLL FREE **1-866-645-9770**

GLK Digital Torque Screwdriver

Series GLK Digital Torque Screwdrivers
60, 250, 500 cN-m capacities

Standard Features

- Rugged, high quality production tools
- High accuracy $\pm 1.5\%$ F.S. both CW and CCW directions
- Selectable units, ozf-in, lbf-in, cN-m
- Peak, peak with auto zero reset and Real Time modes
- Five programmable torque presets ideal for frequent operations.
- Pass/Fail mode counts fasteners tightened within programmed High/Low limits, using LED and audible alerts
- ISO-6789 Compliant
- Kit includes screwdriver with 1/4" square drive, 1/4" square drive to 1/4" hex magnetic adapter, Phillips tip, battery, carrying case and calibration certificate traceable to NIST
- Optional ratchet (RA2) with 1/4" square drive, CW, CCW and fixed operation is available

KTC GLK Digital Torque Screwdrivers are compact, lightweight, and feature, LED and audible alarms, ergonomic handle, push button controls, and are battery powered.

KTC digital torque screwdrivers measure torque in peak or real time modes. Auto zero mode resets peak measurements automatically (1~10 seconds). Selectable units of ozf-in, lbf-in, and cN-m.

Five programmable torque presets stored in memory enable the user to check frequently used values. The presets alert the user with an intermittent signal at 90% and a continuous signal at 100% of the preset torque value using LED and audible indicators which enable users to tighten to within 10% of a preset torque value.

Pass/Fail mode counts the number of fasteners tightened within programmed high and low torque limits.

Optional ratchet (RA2) with 1/4" square drive, CW, CCW and fixed operation is available

For higher accuracy and data output, see DID-4 digital torque screwdrivers.



RANGES

Accuracy $\pm 1.5\%$ F.S., ± 1 LSD

Model No.	GLK060E	GLK250E	GLK500E
<u>ozf-in</u>	0.9~85.0	3.5~354.0	7.1~708.0
<u>lbf-in</u>	0.05~5.31	0.22~22.13	0.44~44.25
<u>cN-m</u>	0.60~60.00	2.5~250.0	5.0~500.0

SPECIFICATIONS

Specifications

Accuracy	$\pm 1.5\%$ F.S.
Measuring direction	CW with display facing you, CCW with display facing away from you
Measuring unit	Selectable lbf-in, lbf-ft, kgf-m, N-m
Data Memory	5 (storable Target torque values), 1 (Pass/Fail Mode)

Auto Shut OFF	Power automatically turns off after 2 minutes of non-use
Battery	Lithium coin battery CR2354
Battery Life	Approx. 2 months (100 usages per day)

DIMENSIONS

[GLK Digital Torque Screwdriver Dimensions](#)

IMADA, Inc. 3100 Dundee Rd., Suite 707, Northbrook, IL 60062 © Copyright 2025
ISO 9001 Registered & ISO/IEC 17025 Accredited Phone: 224-332-3160 Fax: 847-562-0839