



GRAINGER APPROVED GRAINGERCHOICE

Commercial Pressure Gauge:
Corrosion-Resistant Case, 0 to
160 psi, 2 in Dial, Dual

Item #4FMV1 Mfr. Model #4FMV1
UNSPSC #41112403 Catalog Group #D1358
Catalog Page #571

Country of Origin China. Country of Origin is subject to change.

Web Price
\$37.50 / each

Qty
1

Add to Cart

☒ Ship

☐ Pickup

Expected to arrive Tue. Nov 08.
Ship to 78613 | Change

Shipping Weight 0.24 lbs
[Ship Availability Terms](#)

Add to List

Technical Specs

Item	Commercial Pressure Gauge	IP/NEMA Rating	Not Rated
Nominal Dial Size	2 in	Primary Pressure Range	0 to 160
Accuracy	+/-3-2-3%	Dry Dampening Feature	None
Gauge Case Material	304 Stainless Steel	Vibration Resistance	None
Process Connection Type	NPT	Dial Color	White
Process Connection Gender	Male	Pressure Gauge Type	General Purpose Dial Pressure Gauge
Lens Material	Acrylic	Liquid-Filled Case	No
Process Connection Size	1/4 in	Gauge Case Liquid	None
Field Fillable	No	Panel-Mountable	No
Process Connection Location	Center Back	Socket Material	316 Stainless Steel
Case Color	Silver	Sensor Material	316 Stainless Steel

Case Color	Silver
Application	Test and Measurement
Primary Scale Units	psi
Accuracy Scale	Mid-Scale
Ambient Operating Temperature Range	-40 Degrees to 150 Degrees F
Bezel Material	Crimped Stainless Steel
Blowout Safety Back	No
Cleaned for Oxygen Service	No
Freeze Resistant Movement	No
Hazardous Location Rating	Not Rated
Includes Calibration Certificate	No

Sensor Material	316 Stainless Steel
Includes Mounting Hardware	No
Includes Vent Plug	No
Mounting Type	Stem-Mount
Non-Sparking	No
Pressure Range Type	Pressure
Primary Scale Minor Graduations	2
Removable Bezel	No
Scale Type	Dual
Secondary Pressure Range	0 to 1, 100
Secondary Scale Units	kPa

Compliance and Restrictions



WARNING Cancer and Reproductive Harm -
www.P65Warnings.ca.gov

Documentation



[Grainger Choice Pressure and Vacuum Gauge Selection Guide](#)