

JOHNSON Model 40-6001 Specifications / Features

- Accuracy: $\pm 1/16"$ ($\pm 2\text{mm}$)
- Battery Life: 5,000 Measurements
- Calculated Measuring: Addition/Subtraction, Area, Volume, 3 Pythagoras Functions (2-Point, 3-Point, 3-Point Partial)
- Dimensions: 4.1" x 2.4" x 1.3" (104 x 61 x 33mm)
- Indirect Measuring: Pythagoras Functions: Front, Rear, Tripod Thread
- IP Protection Class: 54
- Laser Classification: Class II
- Laser Wavelength: 650nm (Red)
- Maximum Power Output: $<1\text{mW}$
- Measurement Reference Settings: Front, Rear, Tripod Thread
- Measuring Types: Single Distance, Min/Max, Continuous Measuring, Sound Activated Mode, stakeout Function (2 settings)
- Power Supply: 1 9V alkaline battery (included)
- Temperature Range Storage: -4°F to $+140^{\circ}\text{F}$ (-20°C to $+60^{\circ}\text{C}$)
- Temperature Range Usage: $+32^{\circ}\text{F}$ to $+104^{\circ}\text{F}$ (0°C to 40°C)
- Tripod Screw Thread : 1/4" – 20
- Units of Measure: Inches, Feet + Inches, Metric
- Weight: 1.5lbs (0.6kg)
- Working Range: 165' (50m)