

TORQOMETER® TORQUE WRENCHES



US Reading/Standard 2% Accuracy

- Dial torque wrenches allow the user to easily apply and monitor torque
- Long-lasting performance given minimal component contact
- Steel welded bodies with bright nickel-chrome finish
- Heat treated dial guards protect the dial crystal from damage
- Patented torsion bar machined from aircraft quality alloy steel for long life and precise performance across the entire scale
- Wide selection of models...from 1/4-1-1/2" drives...ranges, scales, and dial configurations...there is a dial wrench to cover nearly every need

Square Drive, inches	Basic Models Stock No.	Follow up Models Stock No.	Signal Models Stock No.	Range	Increments	Length, inches	Width, inches	Head Depth, inches	Storage Case
1/4	TE1A	TE1FUA	—	15 in-lb	1/4 in-lb	9-29/32	2-11/16	1-1/4	PB9
1/4	TE3A	TE3FUA	—	30 in-lb	1/2 in-lb	9-29/32	2-11/16	1-1/4	PB9
1/4	TE6A	TE6FUA	—	75 in-lb	1 in-lb	9-29/32	2-11/16	1-1/4	PB9
1/4	GTE6A	—	—	75 in-lb	1 in-lb	9-29/32	2-11/16	1-1/4	PB9
3/8	TE12A	TE12FUA	TE12LA	150 in-lb	2-1/2 in-lb	9-29/32	2-11/16	1-1/4	PB9
3/8	TE25A	TE25FUA	TE25LA	300 in-lb	5 in-lb	9-29/32	2-11/16	1-1/4	PB9
3/8	TE50A	TE50FUA	TE50LA	600 in-lb	10 in-lb	12-1/2	2-11/16	1-1/4	PB9
3/8	TE12FA	TE12FFUA	TE12FLA	12 ft-lb	1/2 ft-lb	9-29/32	2-11/16	1-1/4	PB9
3/8	TE25FA	TE25FFUA	TE25FLA	25 ft-lb	1/2 ft-lb	9-29/32	2-11/16	1-1/4	PB9
3/8	TE50FA	TE50FFUA	TE50FLA	50 ft-lb	1 ft-lb	12-1/2	2-11/16	1-1/4	PB9
1/2	TE51	TE51FU	TE51L	600 in-lb	10 in-lb	15	2-11/16	1-5/16	—
1/2	TE51F	TE51FFU	TE51FL	50 ft-lb	1 ft-lb	15	2-11/16	1-5/16	—
1/2	TE100	TE100FU	TE100L	100 ft-lb	1 ft-lb	16	2-3/4	1-3/8	PBR5
1/2	TE175	TE175FU	TE175L	175 ft-lb	2-1/2 ft-lb	18-3/4	2-3/4	1-3/8	PBR5
1/2	GTE175	—	—	175 ft-lb	2-1/2 ft-lb	18-3/4	2-3/4	1-3/8	PBR5
1/2	TE250	TE250FU	TE250L	250 ft-lb	5 ft-lb	23-3/4	2-3/4	1-3/8	PB8A
3/4	TE352A	TE352FUA	TE352LA	350 ft-lb	5 ft-lb	29-7/8	3-1/4	1-25/32	—
3/4	TE602A	TE602FUA	TE602LA	600 ft-lb	10 ft-lb	40-7/8	3-1/4	1-25/32	PB39
1	TE803**	TE803FU**	TE803L**	800 ft-lb	10 ft-lb	66-13/16	3-9/16	2-1/32	—
1	TE1003†	TE1003FU†	TE1003L†	1,000 ft-lb	10 ft-lb	66-13/16	3-9/16	2-1/32	—
1	TE1503†	TE1503FU†	TE1503L†	1,500 ft-lb	25 ft-lb	80	4-13/32	2-1/8	—
1	TE2003†	TE2003FU†	TE2003L†	2,000 ft-lb	25 ft-lb	80	4-13/32	2-1/8	—
1-1/2	TE2005†	TE2005FU†	TE2005L†	2,000 ft-lb	25 ft-lb	80	3-9/16	2-3/8	—
1-1/2	TE3005	TE3005FU**	TE3005L**	3,000 ft-lb	50 ft-lb	140	5-1/2	2-13/16	—

Wrenches in chart do not include certificate of calibration. Wrenches with a certificate of calibration are available by adding "C" to the end of the stock number.

*Does not include square drive dimension.

†Includes separately packed 92TCQA 5" tubular extension handle.

Basic model = 1 needle Follow-up = 2 needles Signal = signal light GTE models feature a black oxide finish

**Includes separately packed 92TCQA 4" tubular extension handle.

TE3005 includes 94TCQA 10" extension handle