

MITUTOYO

Digital Indicator, Series Series 543, Range 0 in to 0.5 in, Back Type Removable Flat

Item #4GPY1 Mfr. Model #543-392B  
UNSPSC #41111907 Catalog Page #2331



Country of Origin Japan. Country of Origin is subject to change.

These digital indicators are provided with a back lug for mounting and positioning. Back lugs can be clamped into position onto holders and transfer stands.

Technical Specs

|                                   |                      |
|-----------------------------------|----------------------|
| Item                              | Digital Indicator    |
| Range                             | 0 in to 0.5 in       |
| Resolution                        | 0.001 mm, 0.00005 in |
| IP Rating                         | IP42                 |
| SPC Output                        | Yes                  |
| Data Output Type                  | Cable                |
| Long Form Calibration Certificate | No                   |
| Back Type                         | Removable Flat       |
| Dial Size                         | 66 mm W x 83.2 mm H  |
| Dimension Type                    | Inch/Metric          |

|                             |                           |
|-----------------------------|---------------------------|
| Included Certification      | Certificate of Inspection |
| Maximum Measure-ment - Inch | 0.5 in                    |
| Maximum Measure-ment - mm   | 12.7 mm                   |
| Minimum Measurement - Inch  | 0 in                      |
| Minimum Measurement - mm    | 0 mm                      |
| Number of Indicators        | 1                         |
| Operation Type              | Plunger                   |
| Series                      | Series 543                |

Your Price

\$438.90 / each

Qty1

Add to Cart

- ☐ Add Extended Protection Plan for \$112.50 / each [Plan Details & Exclusions](#)
- ☐ Setup Auto Reorder

☒ Shipping ☐ Pickup

Expected to arrive Mon. Aug 23.

Ship to 78660 | [Change](#)

Shipping Weight 0.66 lbs [Ship Availability Terms](#)

Add to List

|                              |              |
|------------------------------|--------------|
| Dimension Type               | inch/millim  |
| Display Type                 | LCD          |
| Accuracy                     | +/-0.0001 in |
| Battery Size                 | SR44         |
| Bezel Type                   | Yes          |
| Case Type                    | Case         |
| Compatible Data Output Cable | 905338       |
| Contact Point Dia.           | 0.375 in     |
| Contact Point Shape          | Radius       |
| Includes                     | Battery      |

|                      |                                              |
|----------------------|----------------------------------------------|
| Variable Resolution  | No                                           |
| Includes Battery     | Yes                                          |
| Includes Case        | Yes                                          |
| Max. Measuring Force | 1.5 N                                        |
| Non-Magnetic         | No                                           |
| Shock Resistant      | No                                           |
| Standards            | C0920, DIN40050 Part 1, IEC 60529, JIS D0207 |
| Stem Dia.            | 0.375 in                                     |
| Stem Thread Size     | #4-48                                        |