



Product Categories / Test Instruments / Pressure & Vacuum Measurement / Pressure & Vacuum Gauges / Industrial & Process Pressure Gauges / Dial Industrial Pressure Gauges / Industrial Pressure Gauge: 0 to 10,000 psi, 2 1/2 in

PIC GAUGES

Industrial Pressure Gauge: 0 to 10,000 psi, 2 1/2 in Dial, Liquid-Filled, 1/4 in NPT Male

Item #20TV37 Mfr. Model # PRO-201L-254U UNSPSC #23151820 Catalog Page #N/A

Country of Origin China. Country of Origin is subject to change.

This gauge features stainless steel case construction to resist corrosion and impact in demanding



Web Price

\$27.73 / each

Qty 1

Add to Cart

☒ Ship

☐ Pickup

Expected to arrive Mon. Dec 27.

Ship to 75201 | [Change](#)

Shipping Weight 0.48 lbs
[Ship Availability Terms](#)

Add to List

Technical Specs

Item	Industrial Pressure Gauge	Field Fillable	No
Nominal Dial Size	2 1/2 in	Process Connection Location	Bottom
Accuracy	+/-2-1-2%	Case Color	Metallic
Gauge Case Material	Stainless Steel	IP/NEMA Rating	Not Rated
Process Connection Type	NPT	Primary Pressure Range	0 to 10,000
Process Connection Gender	Male	Dry Dampening Feature	None
Lens Material	Polycarbonate	Vibration Resistance	Liquid-Filled

Chat with an Agent

Process Connection Size	1/4 in	Dial Color	White
Pressure Gauge Type	Industrial Pressure Gauge	Cleaned for Oxygen Service	No
Liquid-Filled Case	Yes	Freeze Resistant Movement	No
Gauge Case Liquid	Glycerin	Hazardous Location Rating	Not Rated
Panel-Mountable	No	Includes	Vent Plug
Socket Material	Copper Alloy	Includes Calibration Certificate	No
Sensor Material	Copper Alloy	Includes Mounting Hardware	No
Accuracy Grade	ASME B40.100 Grade A	Includes Vent Plug	Yes
Series	201L	Manufacturer Warranty Length	1 yr
Application	General Purpose	Mounting Type	Stem-Mount
Primary Scale Units	psi	Non-Sparking	No
Accuracy Scale	Mid-Scale	Pointer Color	Black
Ambient Operating Temperature Range	-30 Degrees to 180 Degrees F	Pointer Material	Aluminum
Bezel Material	Stainless Steel	Pressure Range Type	Pressure
Bezel Mounting Type	Fixed	Primary Scale Minor Graduations	200
Blowout Safety Back	No	Removable Bezel	No
Case Depth	1.2 in	Scale Type	Dual

 Chat with an Agent

Case Diameter	2.65 in	Scale Type	bar
Secondary Pressure Range	0 to 689	Standards	ASME
Secondary Scale Units	bar		

Compliance and Restrictions

 WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

 Chat with an Agent